QUALITY CONTROL TESTING EQUIPMENT FOR TEXTILE









Rel. En 2019-06

HISTORY

In 1952 Sir Daniele Messa established Mesdan company in Salò - a manufacturing workshop specialized in the production of textile hand knotters. In the 1960's the company became a gualified mechanical industry under the creative impulse of Sir Daniele Messa's son, Mr Pietro. During those years MESDAN was also very busy in developing reliable mechanical knotters suitable to meet the needs of the new automatic winding machines. In the 1970's MESDAN became a consolidated industrial reality of international prestige, and - in 1975 - its corporate structure was changed into a S.p.A. (joint-stock company) corporate form. Meanwhile MESDAN became the leading supplier of knotters to manufacturers of automatic winding machines all over the world. The 1980's are characterized by the 'knot free' yarn joining technology (the so called "splicing" technology), and Mr Renato Zanca (successor to Mr Pietro Messa as Managing Director) led the company to the realisation of an innovative range of splicing devices, soon becoming internationally recognisable thanks to the "JOINTAIR®" and "AQUASPLICER®" trademarks. Mr Zanca also decided to diversify the company activity by entering the business of textile laboratory equipment, to meet the growing demand for Testing and Quality control. In the 1990's MESDAN became established in the field of Laboratory equipment, and made commercial alliances with the most important companies in this sector. After the acquisition of "Osvaldo Fessia's Omac snc" company - specialized in the production of Lab equipment for the control of yarns and fabrics - MESDAN opened its new division known as MESDAN LAB, and started the production and marketing of a wide range of testing equipment. In 2012 the division expanded further, following the acquisition of the controlling stake in Gavazzi S.r.l., an Italian manufacturer of top quality laboratory dyeing & finishing machines. In 2012 MESDAN celebrated its 60th anniversary, acquired the major stake of "Gavazzi S.r.l." - a leading company in dyeing & finishing quality control - and launched the new MESDAN DYELAB line. In 2013 MESDAN joined the "Savio" group of companies.

Mesdan Italy has reached a leading position in the field of yarn joining technology in over sixty years of research & development. Nowadays the 100% "knotless" plied yarn concept leads inevitably to Mesdan splicers, which are considered as a point of reference, thanks to their vanguard technology, workmanship quality, performance reliability and consistency. At present the company consists of two different business units: "Mesdan Yarn Joining Solutions", and "MESDAN LAB" laboratory equipment line.

"Mesdan Yarn Joining Solutions" line includes the complete range of Mesdan splicers - characterized by their registered trademarks: JOINTAIR[®], AQUASPLICER[®], HOT JOINTAIR[®], and MOISTAIR[®] - which are designed in the automatic version (for automatic winders) and in the semi-automatic version for trackmounted installations (for textile machines, where automatic splicing is not possible).

"MESDAN LAB" laboratory equipment line includes a wide range of instruments, suitable for testing fibers, yarns, fabrics and garments, in both traditional and technical textiles. With over two decades track in the field of testing, "MESDAN LAB" can be considered today one of the leading international manufacturers of laboratory instruments.



OPTIMISE YOUR QUALITY, FROM FIBRES TO FABRICS

"MESDAN LAB" is a division of Mesdan S.p.A. renowned designer of yarn joining solutions.

Mesdan entered the textile laboratory business in the early nineties, to meet the growing demand in the market for quality control assurance with the acquisition of "OMAC snc", a company located in Biella (Northern Italy) specialised in the production of testing equipment. Since then MESDAN has designed a complete range of equipment for the analysis of textile materials (fibres, yarns, traditional and technical fabrics), nonwoven, leather, etc., in compliance with International Standards.

"MESDAN LAB" instruments stand out for their industrial design and sound quality that guarantee accurate performances in the long run. The **"MESDAN LAB"** line is produced with particular attention to the environment, in conformity with the safety standards integrating operator-friendly solutions.

In 2004 Mesdan obtained from Det Norske Veritas (DNV) the certification about Quality and Environmental Management System in conformity to UNI EN ISO 9001 and UNI EN ISO 14001, with validity for design, manufacture and calibration of textile laboratory instruments.

Following the acquisition of "Gavazzi", a new range of laboratory dyeing equipment called MESDAN DYELAB SYSTEMS was launched. This range is distinguished for its outstanding workmanship, top quality components/materials, unique technological solutions and excellent results in terms of dyeing accuracy and repeatability.

In 2019 Mesdan Lab Service was accredited to "ISO 17025 calibration laboratory" by "Accredia - ILAC".

Legend

This catalogue is composed of 4 thematic sections illustrating the **"MESDAN LAB"** testing equipment range according to the material to be tested. More detailed information is available in dedicated brochures, which can be downloaded from our website, or obtained from our sales department.

Pictures and information about the instruments are merely indicative. Mesdan S.p.A. reserves the right to modify these specifications at any time, without notice.

A-Z

FIBRES

р9	Air Flow / Wool fineness	Code	272C	p 17	Manual Slivers & Rovings Reel	Code	159A-159B
p 10	Binocular Microscope 1000X	Code	191H	p 18	Melting Point Apparatus	Code	339C
р 10	Calibration Cottons			p 11	MicroLab / Fibre-yarn analysis	Code	250E
p 12	Classifiber tipo W / Fibre length	Code	330A	р9	Micronaire / Cotton fineness	Code	199C
p 18	Climatest / Lab conditioning chamber	Code	1722	р 10	Microtome	Code	256A
p 14	CONTEST-S / Stickiness tester	Code	3304S	p 13	NATI II / Neps and Trash tester	Code	3280B
р8	Double Comb Sorter / Fibre length	Code	230A	p 17	Oil Extractor	Code	273B
p 17	Electronic Slivers & Rovings Reel	Code	254A-254B	р8	Pressley / Fibre strength	Code	231A
р8	Electronic Torsion Balance	Code	165.720	p 16	Raw Cotton Selector	Code	3282
р9	Fiber Tenso-Lab / Single fibre strength-elongation	Code	331A	p 16	Top Tester / Neps-impurities counting	Code	328A
p 10	Fibre Microscope Kit	Code	250.325	p 16	Trash Analyser	Code	281C

YARNS

p 23	Air-Texturlab / Yarn air texture	Code	3200	p 21	Mobile Vertical Creel	Code	3102
p 34	Aqua-Lab / Moisture regain	Code	2450	p 30	MT Evenness Tester	Code	2341
p.31	ASTM varn standards			p.31	Optional KIT "TWO"	Code	2520,600
p 26	Attrifil III / Yarn friction	Code	2330	p.31	Planofil / Yarn conical table	Code	2520
p 24	Auto Cop Changer (ACC)	Code	299A	p 42	Polar Evo Wind-I ab	Code	3374D
p 27	Autodyn II Plus / Automatic strength tester	Code	2514A	p 40	Ring Lab / Mini ring spinning	Code	3108A
p.39	Coiler	Code	337A.6	p 33	Scirocco / Automatic regain oven	Code	172B
n 22	Count Analyser II / Count tester	Code	1666	n 32	"Special" Yarn Sample Winder	Code	171B
n 22	Count Lab Software / for count test	Code	165 630	n 29	Splice Scanner III	Code	2553
n 38	Dve Scanner / Yarn-knit (Dve) uniformity	Code	2940A-B	n 32	"Standard" Yarn Sample Winder	Code	171A
p 20	Electronic Wrap Reel for Yarns	0000	2310/18	n 21	Stationary Adjustable Yarn Tensioners	Code	161M 330
n 21	Fixed Tensiometer	Code	161M 334	n 39	Stiro Roving Lab / Miniature draw frame	Code	3371
n 20	Hand Driven Wran Reel	0000	101111.001	n 28	Tenso-Lab 4 / Tensile strength tester	Code	2512F
n 25	Hand-operated Twist Tester	Code	2531D	n 25	Twist Lab / Semi-automatic twist tester	Code	25310
n 35	Hardness Tester	oouc	20010	n 41	Twister Lab / Two for one lab twister	Code	3373
p 35	Humy Tester III	Code	1850	n 24	Twistmatic II / Full Automatic twist tester	Code	2532
p 33 n 41	Lah Knitter / Varn-knit (Dve) uniformity	Code	204F	p 2 4	Video Analyser / Fibre-yarn-fabric analysis	Code	2500
p 30	Laboratory Carding Machine	Code	2346	p 23	Water-Texturlab / Varn water texture	Code	3200
p 35	Liboccio / Sami automatia ragain avan	Code	2450	μ23 n 10	Wind Lab	Code	3200
p 30	Mini Accombly Lab (Mini accombly winder	Code	2400	p 40	Vern Data Logger (VDL)	Code	2074
μ40	WITH ASSETTING Law / WINT assembly Winder	Code	337ZA	ι μ Ζ Ο	iani Dala Lugger (IDL)	Code	3115

FABRICS

p 69	45° Flammability Tester	Code	3392C	p 71	Integrated Sweating Guarded Hot Plate System	Code	3123B
p 65	AATCC/ISO Crease Appearance Replicas	Code	310.94	p 68	ISO Flammability Lab	Code	3392E
p 65	AATCC/ISO Seam Smoothness Appearance Replicas	Code	310.96	p 67	Linear Cut Resistance Tester	Code	3394B
p 65	AATCC/ISO Smoothness Appearance Replicas	Code	310.74	p 56	MacroLab / Yarn-fabric analysis	Code	250F
p 54	Air Tronic Plus	Code	3240C-E-F	p 50	Martindale	Code	2568
p 72	ANDI Thermal Manikin			p 57	Microscope for fabrics	Code	191G
p 46	Autodyn II / Automatic tensile strength tester	Code	2514	p 64	Multifibre DW 010	Code	257.424
p 72	Automotive Thermal Comfort			p 64	Multifibre TV	Code	257.426
p 63	Autowash II / Wash-Dry colour fastness	Code	311L	p 60	Perspirometer	Code	257A
p 47	Available clamps for Tenso-Lab and Autodyn			p 57	Pick Counters		
p 64	Blue Scale	Code	325.2	p 53	Pneumatic Fabric Stiffness Tester	Code	3396
p 51	Burstmatic / Bursting tester	Code	338E	p 57	Portable Microscope	Code	2604
p 57	Circular Sample Cutter	Code	175B	p 59	Sample Press Lab	Code	1750A
p 49	Crease Recovery Tester	Code	3109	p 60	Scorch Fastness / Sublimation tester	Code	312A
p 49	Crimp Tester	Code	320A	p 65	Soap Powder	Code	310.10
p 58	Crock Meter / Rubbing fastness	Code	2540	p 52	Spray Rating Tester	Code	333A
p 52	Digital electric-hydraulic Bursting Tester	Code	338D	p 64	Standard Adjacent Fabrics		
p 62	Dry Cleaning Machine	Code	310F	p 66	Static Lab	Code	291B
p 72	Drying Rate Tester DRT201			p 61	Sun Lab / Light fastness	Code	325A
p 65	ECE/IEC Reference Detergent			p 70	Sweating Guarded Hot Plate	Code	3123
p 58	Electric Crock Meter / Rubbing fastness	Code	198B	p 44	Tenso-Lab 4 / Tensile strength tester	Code	2512E
p 57	Electronic balance per m ²	Code	165.664	p 45	Tenso-Lab 5000 / Tensile strength tester	Code	2515
p 55	Elmatic / Elmendorf tearing tester	Code	275D	p 53	Thickness-Lab / Thickness tester	Code	1880
p 53	Elmendorf	Code	275A	p 63	Top Loading Home Washer	Code	310H
p 58	Forced Ventilation Conditioning Oven	Code	251G	p 62	Tumble Dryer	Code	3111
p 63	Front-loading Home Tumble Dryer	Code	3111B	p 66	Vapour Permeability Tester	Code	3122
p 67	Glove Cut Tester	Code	3394A	p 69	Vertical Flammability Tester	Code	3392G
p 64	Grey Scales			p 62	Wascator	Code	310B
p 59	Hoff-Lab Press	Code	3370B	p 54	Water Proof	Code	3241C
p 69	Horizontal Flammability Tester	Code	3392D	p 66	Water Vapour Test	Code	3395
p 52	ICI Pilling & Snagging Tester 4 positions	Code	279G	p 49	Wrinkle Recovery Tester	Code	3110
p 67	Impact Abrasion Lab	Code	2563	p 61	Xenon Lab / Light fastness	Code	325E
p 60	Incubator	Code	251L				

MISCELLANEOUS

p 78	"Assmann" Psychrometer	Code	196C	p 82	Portable pH-meter	Code	322C
p 77	Battery Powered Digital Stroboscope	Code	186F	p 83	Portable Thickness Gauges		
p 82	Bench pH-Meter	Code	322L	p 81	Refractometer	Code	266A
p 81	Digital Force Tester	Code	194D	p 80	"Sartorius" analytic Balance	Code	165.702
p 79	Digital Thermometer	Code	244B	p 80	"Sartorius" multi-purpose Balance	Code	165.708
p 78	Electronic Psychrometer	Code	288C	p 80	"Sartorius" precision Balance	Code	165.704
p 74	Electronic Tachometer	Code	1810C	p 78	Sling Psychrometer	Code	196B
p 74	Electronic Tachometer	Code	1810G	p 77	Strobo Lab	Code	186H
p 74	Electronic Tachometer	Code	1810E	p 77	Stroboscope		
p 74	Electronic Tachometer	Code	1810H	p 75	Tensiometer Zivy		
p 76	Electronic Tensiometer DTS			p 80	Thermo Balance	Code	165.502
p 76	Electronic Tensiometer ETB			p 78	Thermo-anemometer	Code	287C
p 75	Electronic Tensiometer ZEF/ZED			p 83	Ultrasonic Cleaning Baths		
p 76	Mechanical Tensiometer DX2			p 82	UV Lamp	Code	189A
p 76	Mechanical Tensiometer ZF2/ZD2			p 82	Viscosimeter	Code	3220
p 83	Melt-Flow Index	Code	339B	p 75	Warp Tensiometer DXK model		
p 79	Optical Pyrometer	Code	296D	p 79	Writing Thermo-hygrograph	Code	180B
р 79	Orbital Shaker	Code	3125A	p 81	Yarn Meter	Code	298E
p 77	Phonometer	Code	243B	p 81	Yarn Meter	Code	298D



Leading supplier of quality control laboratory equipment for physical testing, colour fastness, dyeing and finishing





FIBRES

р8	Pressley / Fibre strength	Code	231A
р8	Double Comb Sorter / Fibre length	Code	230A
р8	Electronic Torsion Balance	Code	165.720
р9	Fiber Tenso-Lab / Single fibre strength-elongation	Code	331A
р9	Micronaire / Cotton fineness	Code	199C
p 9	Air Flow / Wool fineness	Code	272C
p 10	Calibration Cottons		
p 10	Binocular Microscope 1000X	Code	191H
р 10	Microtome	Code	256A
р 10	Fibre Microscope Kit	Code	250.325
p 11	MicroLab / Fibre-yarn analysis	Code	250E
p 12	Classifiber tipo W / Fibre length	Code	330A
р 13	NATI II / Neps and Trash tester	Code	3280B
р 14	CONTEST-S / Stickiness tester	Code	3304S
р 16	Top Tester / Neps-impurities counting	Code	328A
р 16	Trash Analyser	Code	281C
р 16	Raw Cotton Selector	Code	3282
р 17	Electronic Slivers & Rovings Reel	Code	254A-254B
р 17	Manual Slivers & Rovings Reel	Code	159A-159B
р 17	Oil Extractor	Code	273B
p 18	Climatest / Lab conditioning chamber	Code	1722
p 18	Melting Point Apparatus	Code	3390





Pressley Fibre strength

An equipment to determine the resistance of cotton fibres. It is fitted with clamps with 0" and 1/8" distance. The use of Pressley requires a torsion balance with resolution 0.01 mg (code 165.720).

Accessories: calibration cottons (code 199.22).

Reference standards: ISO 3060, ASTM D1445, BS 5116, ASTM D2524

Weight: 3.2 kg Dimensions: (L) 330 x (W) 100 x (H) 125 mm



Double Comb Sorter Fibre length 230A

For the production of staple diagrams for short spun fibres up to 100 mm (4") length.

Determination of fibre length or staple diagram is a decisive factor in defining the spinning quality of raw material and for the setting of spinning machinery.

Reference standards: ISO 920, ASTM D1440, ASTM D1575, IWTO 1-66

Weight: 15 kg Dimensions: (L) 250 x (W) 150 x (H) 140 mm



Electronic Torsion Balance

165.720

High Quality Electronic Torsion Balance. Suitable for very small quantity of fibres, bundles, pieces of

yarns from fabrics and garments.

For the use of Pressley (Code 231A), Double Comb Sorter (Code 230A), and Fiber Tenso-Lab

(Code 331A), this type of balance is needed.

Digital reading.

Weighing capacity: 60 g Accuracy: 0,00001 g

Power supply: 100 up to 230 Vac, 50/60 Hz, single-phase Weight: 7.8 kg Dimensions: (L) 376 x (W) 214 x (H) 316 mm

231A

Fiber Tenso-Lab Single fibre strength-elongation

Single fibre electronic strength tester suitable for natural and synthetic fibres.

Complete with load cell of 500 cN, 0,5 class accuracy. Traction speed range from 0,001 to 1000 mm/min.

300 mm stroke.

A "Kit Cotton Fibre Bundle", special 0" and 1/8" clamps for testing cotton fibres, Pressley method, 100 N load cell are available on demand.

RS232 port and software are included (PC is available as optional).

Reference standards: UNI EN ISO 5079, UNI EN 13895, UNI EN 12751, ISO 3060, BS 3411, BS 4029, BS 5116, ASTM D1294, ASTM D1445, ASTM D2524, ASTM D3106, ASTM D3217, DIN 53843-2

Power supply: 115 V or 230 V, 50/60 Hz, single-phase Weight: 46 kg Dimensions: (L) 590 x (W) 450 x (H) 770 mm

Micronaire Cotton fineness

1990

Device for the control of the cotton fibre fineness. Measurement from 2.5 to 7 micronaire index.

Calibration chart prepared using USDA cotton references. Test with 2.5 grams sample.

Complete with electric vacuum-pump generating the air flow. Non hygroscopic plug for checking instrument.

The use of MICRONAIRE requires an electronic scale with 0.01 g accuracy (**Code 165.708**).

Reference standards: ISO 2403, ASTM D1448, BS 3181-1

Power supply: 230 Vac, 50 Hz, or 115 Vac, 60 Hz (to be specified at order) Weight: 26 kg Dimensions: (L) 240 x (W) 330 x (H) 580 mm

Air Flow Wool fineness

272C

Device for the control of the wool fibre fineness. Measurement from 16 to 36 microns.

Test with 2.5 grams sample.

Complete with electric vacuum-pump generating the air flow. Non hygroscopic plug for checking instrument and correction of reading.

The use of AIR FLOW requires an electronic scale with 0.01 g accuracy (**Code 165.708**).

Reference standards: ISO 1136, IWTO 6, IWTO 28, ASTM D1282

Power supply: 230 Vac, 50 Hz, or 115 Vac, 60 Hz (to be specified at order) Weight: 29,5 kg

Dimensions: (L) 240 x (W) 330 x (H) 580 mm



Calibration Cottons

Suitable for the calibration of cotton examination instruments, in accordance with USDA standards.

For calibration of fiber fineness:

American Upland Micronaire 5.5	Code	199.2
American Upland Micronaire 4.5	Code	199.4
American Upland Micronaire 3.5	Code	199.6
American Upland Micronaire 4	Code	199.8
American Upland Micronaire 2.6	Code	199.14
American Upland Micronaire 5.0	Code	199.18

For calibration of Micronaire, resistance, elongation and length:

C39 American Upland: Micronaire 3,39, 25,1 g/tex, 7,1% elongation, 1,12 inch S.L. at 2,5%, 0,53 inch S.L. at 50%

Code 199.22

256A

For calibration of resistance and elongation:

L2 American Upland: 18.0 g/tex, 5.6% elongation Code 199.28 M1 American Upland: 30.8 g/tex, 6.4% elongation Code 199.26

Binocular Microscope 1000Х 191н

Binocular model, suitable for fibre analysis.

The combination of eyepieces and lenses enables a magnification range from 40X to 1000X.

Equipped with micrometric stage carrier for object prospecting.

Power supply: 100 up to 240 Vac, 50/60 Hz, single-phase Weight: 4 kg $\,$

Dimensions: (L) 120 x (W) 200 x (H) 350 mm

Microtome

Hand operated model to produce fibre samples of predetermined length for microscopic analysis.

Reference standards: ISO 137, UNI 5423-64

Weight: 0.16 kg Dimensions: (L) 120 x (W) 50 x (H) 10 mm

Fibre Microscope Kit 250.325

Complete kit of all accessories needed for the analysis of fibres length and section. It includes: 100 glasses and 200 glass covers one oil package tool kit (tweezers, scissors etc.) needles tool for preparation of sections of fibres and yarns tool for fabric observation











High performance computerised system conceived for the analysis of fibres and yarns.

Equipment suitable to: perform in a fast and easy way the fineness analysis of single fibres; identify the different fibres contained in a blend and analyse the composition percentage; check the purchased material and identify the type of fibre; analyse the yarn structure and detect possible defects; measure the count of circular section yarns and filaments in Dtex or den; check and measure the quality and shape of Lycra or synthetic multifilament single threads; analyse the compactness of non-woven fabrics; analysis of yarn and fibre sections; measure section surfaces and perimeters; analyse mechanical parts (i.e. needle points, spinnerets, etc); process, store and print the produced measurements and the minimum, medium and maximum values, CV% and distribution graphs.

The system is composed of:

LEICA Biological Microscope: magnification range on screen from 195X to 2830X, with slide movement device with micrometric regulation, polarising light, for fibres and yarns analysis, etc.

PC complete with, LCD monitor and photographic quality printer.

Professional digital colour camera, 1/2.33", CMOS, 16.0 Mpixel, USB 3.0, to acquire images from microscope.

Software for the image acquisition, the production of measurements and comments on the stored images and measurements directly on the live images, the statistic analysis of the acquired measurements.

Fibre Microscope Kit (Code 250.325) for the microscopic analysis (fibres, yarns, and fabrics). Instructions for sample's preparation.

Reference Standards: ISO 137, UNI EN 12751, UNI 5423, UNI ISO 1130, ASTM D629, ASTM D2130, ASTM D276, AATCC 20, IWTO 8, IWS TM24, NIKE (section H, fiber content testing) requirements)

Power supply: 100 up to 240 Vac, 50/60 Hz Weight: 50 kg Dimensions: (L) 1600 x (W) 700 x (H) 700 mm

Optional:

63X LEINS enabling 2830X magnification		
on screen.	Code	250.336
C-STEP CONNECTOR WITH 0.5X LENS		
allows to halve the magnification on screen		
and double the sample field of vision.	Code	250.338
Set of 50 slides.	Code	191.50
Set of 200 slide covers.	Code	191.52
Immersion oil bottle.	Code	191.54
Pack of paper for printer.	Code	250.18
Set of cartridges for printer.	Code	250.322



	N°	Mean	Mode	Min	Max	St.Dev.	CV%	IC.(95%)	%
Wo	76	18,43	17	12	34	3,79	34,54	2,06	26,09
Other	28	19,39	16	11	35	7,45	62,15	4,22	29,81
Ws	96	12,14	13	8	25	2,18	18,19	0,95	44,09

Example of micronaire analysis of a blend made of 3 different fibres









Fibrogram



Measuring unit



Automatic instrument suitable to measure the length of any type of fibre (animal, vegetal or synthetic). Specifically conceived for testing cashmere fibres or similar. Measuring range: up to 80 mm.

Graphic data from each individual test:

Fibrogram Staple diagram Histogram

Statistics:

Mean Minimum (Min.) Maximum (Max.) Range (R) Standard deviation (s) 95% confidence limits (Q965%)

Testing results:

Mean length (ML) Upper half mean length (UHR) Span length at 2,5% (SL 2,5%) Span length at 50% (SL 50%) Span length at 66% (SL 66%) Uniformity ratio (UR%) Uniformity index (UI%) Short fiber content (SFC%)

Classifiber is PC dependent. PC and dedicated software are supplied with the instrument. Complete of flat carding for sample preparation and accessories kit. Fibre length readable in mm and inches. Excellent correlation with manual testing but faster (average of 3 tests): only 20 seconds.

Reference standards: ISO 6989, ISO 4913, ASTM 1447, UNI 10141, FZ/T 20028.

Power supply: 115 Vac or 230 Vac, 50 Hz or 60 Hz, single-phase Weight: 50 kg

Dimensions: (L) 1600 x (P) 750 x (H) 720 mm



Suitable for cotton, synthetic and blended slivers as well as raw cotton material.

By means of an optoelectronic system, NATI II measures Neps and Trash in different size classes:

 \geq 0,50 mm; \geq 0,70 mm; \geq 1 mm for Neps

≥0,25 mm; ≥0,50 mm for Trash.

Equipped with internal memory, USB port (for data saving), and user-friendly digital touch screen display.

Test results are available in .xls format, and can be printed by the mini thermal printer, Code 3280A.136 (available as optional).

Specifically designed to be fast, reliable and easily transportable to the production floor for continuous testing and assessment of Neps and Trash at different process stages.

NATI II is the only instrument presently available on the market measuring and classifying automatically Neps and Trash content in samples of large size up to 6 m of sliver (30 g approximately, depending on sliver count).

NATI II is the only Neps tester for which **no manual preparation** of the sample is required, thus ensuring total reliability of results (it is known that the ability of the operator can lead to 25%-50% variation in the results).

Transportable and fast in testing large size samples (it takes less than 2 minutes to test 2 g of sliver), NATI II makes daily control of carding department feasible, thus enabling a better quality of carding operation and a better planning of card maintenance.

User-friendly, NATI II does not require any skill for operation and preliminary operation before testing.

Raw cotton testing: the use of the optional "Raw Cotton Selector" (**Code 3282**) enables you to prepare 2/2,5 g samples in short time and without the influence of operator's ability on results.

NATI II fits an enlarged fibre waste which box, especially conceived for testing large size samples, is recommended specifically for combed cotton and synthetic slivers due to the small content of Neps/g.

NATI II is endowed with a brushless motor (of easy maintenance) granting unchanged performance even after several thousand hours of test.

Optional:

Opening roller B174N for Cotton	Code	3280.168
Opening roller S43N for Polyester	Code	3280.169
Mini thermal printer	Code	3280A.136
Raw Cotton Selector	Code	3282
Trolley	Code	3280.900
Electronic high precision sartorius balance	Code	165.704

Power supply: 115 Vac or 230 Vac, 50 Hz or 60 Hz Weight: 40 kg

Dimensions: (L) 400 x (W) 379 x (H) 700 mm



Fully automatic high volume testing equipment designed to detect, measure, classify and grade cotton stickiness (honeydew/ sugar content).

Unique equipment providing **cotton stickiness risk probability** on the basis of its grade, enabling spinners to anticipate proper actions (how to process & blend different cotton bales).

It ensures fast testing and very repeatable and consistent results.

It is a precious tool for spinning mills, cotton traders, textile institutes, R&D labs and other cotton grading, arbitration and classification institutions.

Cotton STICKINESS phenomenon (also called "sugar" - honeydew) is analysed by means of a thermomechanical method, able to detect stickiness deposits of different origin in the fibre web, and to classify them in 5 classes by size, from 1 (small) to 5 (large). Stickiness - affecting the spinning process - is graded by the specific software, giving more importance to larger than to smaller deposits.





CONTEST-S makes the difference in the working principle, since it provides a counting per gram of the sticky points and their sizes by simulating the carding process like in a real spinning process.





STICKINESS GRADE	SPINNING RISK PROBABILITY
0-50	No Risk
51-100	Low
101-160	Medium
161-250	High
251-500	Very High
>501	Extremely High



Measuring principles and testing method:

Thermodetection of sticky deposits in the fibre web.

 $3.5~{\rm g}\,/\,10~{\rm m}$ sample pressed through two $37^{\circ}{\rm C}$ heated drums revolving in opposite directions.

The sticky deposits adhere on the drums' surface, and are optically examined by means of a laser beam.

Sticky points are analysed (amount and size) by the software. Subsequently sticky points are eliminated by means of two rotative brushes and a blade-mechanism, to ensure automatic cleaning of the drums' surface, in order to avoid double counting and contamination of subsequent measurements.

Detection sensor of fibrous material at the end of the test allows to monitor and warn about unproper cleaning of the drum surface.

The heating of the drums is achieved by a special (patented) friction system of two moveable and adjustable brushes, which permit to rapidly reach the correct starting temperature, and maintain it stable during the test, thus ensuring measurement reliability and accuracy.

Reference Standards:

Stickiness: UNI EN 14278-3 (Method using an automatic thermodetection rotating drum device).

The sticky deposits are counted, classified and graded by the Stickiness Tester software as follows:

Sticky points classes: all deposits are divided in 5 classes by size, from 1 (small) to 5 (large).

Sticky points/g: the total amount of sticky points, in total and per class, is then converted into unit / g.

Sticky grade: stickiness is graded by the software giving more importance to larger than smaller deposits. Sticky grade is an important real value, which enables to immediately identify cotton stickiness, for an easier bales management.

Sticky points average size.

Techinical features:

Stickiness	total count / g
Stickiness average size	mm
Stickiness classes	5 classes (from 1 to 5)
Stickiness grade	based on stickiness counting and classification
Testing speed:	about 30 seconds / sample

Power supply: 230 Vac, 50/60 Hz, single-phase, 2 kW Weight: 340 kg Dimensions: (L) 1510 x (W) 960 x (H) 1410 mm



Top Tester Neps-impurities counting 328A

For quick and accurate counting of impurities and neps in wool, cotton and synthetic fibre tops.

Adjustable distance between rollers ranging from 42 to 260 mm. Adjustable speed from 5 to 12 m per minute.

Predetermined drawing standard value: 6.35 (other values are available on request).

Impurities are counted and classified through a series of 6 electronic counters.

Magnifying lens, fitted with light, included Code 328.2

Optional:

Printer for print-out of defects in tops Code 3280A.136

Power supply: 115 Vac or 230 Vac, 50 Hz or 60 Hz, single-phase Weight: 120 kg

Dimensions (L) 700 x (W) 800 x (H) 1400 mm



Trash Analyser

281C

To determine the percentage content of trash, lint, non-fibre material in raw cotton samples of about 100 g. Also used to determine non-fibre content of synthetic fibres and to open and clean fibres for further testing. The analyser uses the carding principle of separation of lint and non lint content by means of air.

Power supply: 400 Vac, 50 Hz, three-phase + ground Weight: 190 kg Dimensions: (L) 640 x (W) 950 x (H) 1300 mm



Raw Cotton Selector

3282

Small laboratory carding machine to prepare a cleaned and homogenous sample of raw cotton, to be used with NATI II for testing of neps content.

Raw Cotton Selector is ideal for the preparation of samples to be tested on a sticky cotton thermodetector (Honey Dew analysis). Generally speaking Raw Cotton Selector is ideal for preparation of clean fibre samples to be tested.

Power supply: 115 Vac or 230 Vac, 50/60 Hz, 30 VA Weight: 25 kg Dimensions: (L) 625 x (W) 420 x (H) 250 mm

Electronic Slivers & Rovings Reel

254A-254B

Available with drum circumference of either 1 yard (**Code 254B**) or 1 metre (**Code 254A**). Adjustable drum speed from 0 to 100 m/min., with ± 1 cm accuracy. Designed to prevent any possible drawing of the fibre sample.

Equipped with digital counter and cutter for accurate cutting of the sliver sample.

Power supply: 115 Vac or 230 Vac, 50/60 Hz single-phase Weight: 52 kg

Dimensions: (L) 450 x (W) 300 x (H) 500 mm



Manual Slivers & Rovings Reel

159A-159B

Hand-driven reel for slivers and rovings. Available with either 1 metre (**Code 159A**) or 1 yard

(Code 159B) drum circumference.

Fitted with digital counter and cutter for accurate cutting of the sliver sample.

Weight: 17 kg Dimensions: (L) 330 x (W) 270 x (H) 600 mm

Oil Extractor

273B

Electronic instrument with digital reading of set temperature for quick determination (in about 15 minutes) of oil/grease/ lubricant percentage content in fibres and yarns.

The use of an analytic balance with accuracy 0.0001 g is essential with this instrument (Code 165.702).

Accessories:

Set of 50 aluminium plates (Code 273B.2).

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 8 kg Dimensions: (L) 250 x (W) 150 x (H) 430 mm







Climatest Lab conditioning chamber

Laboratory instrument for the conditioning of all textiles, such as raw fibres, yarns on spools and hanks, fabrics and garments in general, at constant temperature and humidity, according to ISO standards.

1722

Climatest is supplied complete with two shelves.

Equipped with inner glass door for inspection.

Adjustable temperature ranging from $+5^{\circ}$ C to $+80^{\circ}$ C, accuracy $\pm 0.5^{\circ}$ C at 37° C.

Relative humidity ranging from 20% R.H. to 90% R.H., accuracy \pm 3%. Digital reading of temperature and humidity. Automatic water inlet into the reservoir.

Reference standards: UNI EN ISO 139, ASTM D1776, UNI EN 12280-3

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 130 kg $\,$

Inner dimensions: (L) 593 x (W) 522 x (H) 633 mm External dimensions: (L) 960 x (W) 760 x (H) 1390 mm





Melting Point Apparatus 339c

To determine the melting point of fibres and synthetic yarns and classify them.

Measuring range: from $+30^{\circ}$ C to $+300^{\circ}$ C, accuracy $\pm 0.1^{\circ}$ C. Complete with magnifying lens to check the melting point, and 100 slides.

Reference standards: ASTM D789, ASTM D2117, FIAT 50568

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 6 kg $\,$

Dimensions: (L) 280 x (W) 190 x (H) 220 mm

YARNS

p 20	Electronic Wrap Reel for Yarns		
p 20	Hand Driven Wrap Reel		
p 21	Stationary Adjustable Yarn Tensioners	Code	161M.330
p 21	Fixed Tensiometer	Code	161M.334
p 21	Mobile Vertical Creel	Code	3102
p 22	Count Analyser II / Count tester	Code	1666
p 22	Count Lab Software / for count test	Code	165.630
p 23	Air-Texturlab / Yarn air texture	Code	3200
p 23	Water-Texturlab / Yarn water texture	Code	320D
p 23	Yarn Data Logger (YDL)	Code	3115
p 24	Twistmatic II / Full Automatic twist tester	Code	2532
p 24	Auto Cop Changer (ACC)	Code	299A
p 25	Hand-operated Twist Tester	Code	2531D
p 25	Twist Lab / Semi-automatic twist tester	Code	2531C
p 26	Attrifil III / Yarn friction	Code	233C
p 27	Autodyn II Plus / Automatic strength tester	Code	2514A
p 28	Tenso-Lab 4 / Tensile strength tester	Code	2512E
p 29	Splice Scanner III	Code	2553
р 30	MT Evenness Tester	Code	2341
р 31	Planofil / Yarn conical table	Code	2520
р 31	Optional KIT "TWO"	Code	2520.600
р 31	ASTM yarn standards		
р 32	"Standard" Yarn Sample Winder	Code	171A
р 32	"Special" Yarn Sample Winder	Code	171B
р 33	Scirocco / Automatic regain oven	Code	172B
р 34	Aqua-Lab / Moisture regain	Code	2450
р 35	Libeccio / Semi-automatic regain oven	Code	245B
р 35	Humy Tester III	Code	185C
p 35	Hardness Tester		
р 36	Video Analyser / Fibre-yarn-fabric analysis	Code	250D
p 38	Dye Scanner / Yarn-knit (Dye) uniformity	Code	2940A-B
р 39	Laboratory Carding Machine	Code	337A
р 39	Coiler	Code	337A.6
р 39	Stiro Roving Lab / Miniature draw frame	Code	3371
p 40	Ring Lab / Mini ring spinning	Code	3108A
p 40	Wind Lab	Code	3374
p 40	Mini Assembly Lab / Mini assembly winder	Code	3372A
p 41	Twister Lab / Two for one lab twister	Code	3373
p 41	Lab Knitter / Yarn-knit (Dye) uniformity	Code	294E
p 42	Polar Evo Wind-Lab	Code	3374D



Electronic Wrap Reel for Yarns





To prepare yarn skeins of a preset length, that will then undergo testing for the determination of the related count.

Equipped with electronic pre-selector for the automatic stop at the preset length. Supplied complete with a 7-position support creel (spool and small bobbin holder).

Adjustable double-bar yarn tensioner. Plexiglass cover available on demand.

Reference standards: UNI EN ISO 2060, ASTM D1907, ASTM D2260 The electronic wrap reel is available in the following models:

Code	161M
Code	161X
Code	161Y
Code	161W
	Code Code Code Code

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 40 kg Dimensions: (L) 900 x (W) 600 x (H) 600 mm





Hand Driven Wrap Reel

Available reel circumferences:

- 1 meter Code 160M
- 1 yard Code 160Y

Equipped with digital counter for yarn length reading. Supplied with support creel and double-bar yarn tensioner.

Reference standards: UNI EN ISO 2060, ASTM D1907, ASTM D2260

Weight: 35 kg Dimensions: (L) 900 x (W) 600 x (H) 600 mm

Optional for Wrap Reels

Stationary Adjustable Yarn Tensioners

161M.330

Suitable in case of very coarse yarns for which a very high pretension is required (for example carpet yarns), or in case of preparation of texturized synthetic fibres skeins for crimp value testing.

This optional should be fitted on the reel feeding creel in place of the standard double-bar tensioner, or on the yarn guide support.



Fixed Tensiometer

161M.334

Conceived for synthetic yarns, which require an accurate and continuous control of pre-set pretension during wrapping.

Available reading ranges (to be specified at order):

3-12	сN
5-20	сΝ
5-30	сN
10-50	сΝ
10-100	сN



Mobile Vertical Creel

3102

Suitable for feeding different instruments, such as wrap reel, automatic strength tester, automatic twist tester, Attrifil, evenness tester, etc., where it is necessary to simultaneously use large-sized bobbins.

Weight: 22 kg Dimensions: (L) 600 x (W) 600 x (H) 2000 mm



Count Analyser II Count tester 1666



**MESDRN	LAB	**
****	****	*****
07/03/	2017	15:21:09
SIMPLIFY	COU	NT
DTEX (m)	>	(100.00)
Min N.	5:	1390.0000
Max N.	4:	1470.0000
Mean	:	1406.0000
σ	:	35.7771
CV [%]	:	2.5446
Range [%	1:	5.6899
IC%(M95%)):	2.5446
Down Lim:	it:	1334.4458
Up Limit	:	1477.5542
Test	n.	Count
1		1390.0000
2		1390.0000
3		1390.0000
4		1470.0000
5		1390.0000

To determine the count of slivers, rovings, yarns and fabric weight per m². Outputs: single result, minimum, maximum and average, CV%, range%, sigma, I.C. (95%), results out of tolerance. Standard measurement scales are available: Nec/m, Nec/yd,

Nm, Den, Tex, dTex, grain/yd, g/m². Sample length from 1 cm (1 inch) up to 999 m (yard).

According to the weight of the sample to be tested, the following balances are available:

Sartorius balance - 820 g capacity - 0,01g accuracy - pan size Ø 150 mm (suitable for yarns), Code 165.708

Sartorius balance - 320 g capacity - 0,001g accuracy - pan size \emptyset 115 mm (ideal for synthetic filaments and fine yarns count testing), Code 165.704

Other models available on request.

Reference standards: ISO 3374, UNI EN 29073, UNI 8014-2-3-4, ISO 2060, UNI 5114, BS 2471, ISO 3801, ASTM D1907/D3776, UNI EN ISO 2060, UNI EN 12127

Power supply: 115 up to 230 Vac, 50/60 Hz, single-phase Weight: 4.3 kg

Dimensions: (L) 700 x (W) 400 x (H) 200 mm





Count Lab Software for count test

Suitable to determine the count of sliver, roving, yarn and fabric weight per m². Standard measurement scales are available: Nec/m, Nec/vd, Nm, Den, Tex, dTex, Grains/YD, g/m².

Outputs: single result, minumum, maximum and average, CV%, range %, I.C. (95%), out of tolerance results.

Test results are exported to Excel for automatic calculation of statistics (average, minimum, maximum count, C.V.%, sigma, range %, IC%, upper and lower IC% limits).

Output report can be printed and saved. PC minimum features required: Windows Xp, Excel (2000 or Xp) program, one serial and one USB port.

Optional: Sartorius electronic balance with different capacity and accuracy depending on the textile to be tested. **Count Lab Software can be connected to Sartorius balances only.** PC available on request.

Reference standards: ISO 3374, UNI EN 2973-1, UNI 8014-2-3-4, UNI EN ISO 2060, UNI 5114, BS 2471, ISO 3801, ASTM D1907, D3776, D2646, ISO 2060, UNI EN 12127, ISO 9073-1

Air-Texturlab Yarn air texture

3200

To determine the percentage of crimp in all types of textured synthetic yarns.

Air-Texturlab requires the use of an electronic wrap reel of 1 m circumference (**Code 161M**), a forced ventilation oven with internal capacity 250 litres (**Code 251P**) - supplied complete with skein support. The most suitable pretension weights (optional) can be selected from the ones listed in the table below, according to the nominal count.

Reference standards: DIN 53840-1 (up to 500 dtex), DIN 53840-2 (over 500 dtex), UNI EN 14621, ASTM D4031, ASTM D2259

Weight: 10 kg Dimensions: (L) 500 x (W) 20 x (H) 800 mm

Water-Texturlab Yarn water texture 320D

To determine the percentage of crimp in all types of textured synthetic yarns; particularly suitable for nylon textured yarns for stockings. Equipped with a Plexiglas cylinder to be filled with water and a skein holder millimetre bar with 1 mm accuracy. Water-Texturlab requires the use of an electronic wrap reel of 1 m circumference (**Code 161M**) and a set of pretension weights (optional) to be selected according to the nominal count.

Reference standards: BS 6663

Weight: 8 kg Dimensions: (L) 120 x (W) 120 x (H) 800 mm

Optional pretension weights for Air and Water Texturlab 320C 320D

g g	2,5 3	Code Code	320.36 320.2	g g	7 8	Code Code	320.10 320.12
g	4	Code	320.4	g	9	Code	320.14
g	5	Code	320.6	g	10	Code	320.16
g	6	Code	320.8				
Weig	ghts wit	h simpl	e hook				
g	20	Code	320.42	g	300	Code	320.26
g	25	Code	320.38	g	350	Code	320.28
g	50	Code	320.44	g	400	Code	320.30
g	100	Code	320.18	g	450	Code	320.32
g	150	Code	320.20	g	500	Code	320.34
g	200	Code	320.22	g	2500	Code	320.40
ø	250	Code	320.24				

Yarn Data Logger (YDL) 3115

Quality Control Software specifically developed to collect the data of all laboratory yarn testing instruments.



YARNS



Fully automatic computer-based twist tester, for the control of the loading phase, the twist testing,

the change of the yarn length of the bobbin under test, the processing of a complete series of statistical data and for the printing of the related reports.

The instrument, unique for its high quality, can automatically perform serial twist tests on a single package (max. 999 tests) or, if connected to the Auto Cop Changer (ACC) device, **Code 299A**, it can automatically perform multiple tests on several packages (up to 24).

Suitable for all types of spun (ring and open-end) yarns and synthetic filament yarns, both "S" and "Z" twist.

Technical features:

Automatic testing either on one package, or on 24 packages, by means of the Auto Cop Changer (ACC), which guarantees high accuracy and repeatability of results, also eliminating the human error.

Three preselectable test methods:

a) Traditional method: untwisting and retwisting, for single yarns.

b) "Schutz" method: untwisting, retwisting and double countercheck, automatically performed on O.E. spun and worsted wool yarns.

c) Direct method: untwisting, for plied spun yarns, threads and multi-filament yarns.

Twist testing on certain yarn lengths at preset intervals.

Statistical results: average value, minimum value, maximum value, C.V.%, range, standard deviation and alpha coefficient.

Twist results available either in rotations per metre (RPM) or rotations per inch.

Fixed distance between clamps: 50 cm.

PC connection through RS232C serial output.

PC and Printer are available on request.

Reference standards: UNI EN ISO 2061, ISO 2061, ISO 7211-4, ISO 17202, UNI 9067, UNI 9277, UNI 9069, ASTM D1422, ASTM D1423

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Air supply: 6 bar Weight: 25 kg Dimensions: (L) 1060 x (W) 330 x (H) 330 mm

Auto Cop Changer (ACC) 299A

"Auto Cop Changer" (ACC), up to 24 positions, can be connected to Twistmatic II, Attrifil III, Autodyn and Dye Scanner for multiple tests on a lot of packages (up to 24) without operator's attendance.

Very easy to use and suitable for a wide range of yarns.

Available also a 36-position model	Code	299B
Along with the ACC, a creel is required	Code	3102
Power supply: 12 V, DC		
Air supply: 6 bar		
Weight: 17 kg		
Dimensions: (L) 570 x (W) 250 x (H) 230 mm		



Hand-operated Twist Tester



Manual twist tester for twist measurement on single and plied yarns ("S"/"Z"). Two test methods are available:

Traditional "untwisting and retwisting" method, for single spun yarns.

Direct "untwist" method, for plied yarns, threads and multifilament yarns.

Adjustable test length (distance between clamps) from 1 to 50 cm (0.39-19.6 inches). Built-in digital tachometer (battery supplied) and optical sensor with led showing correct zero starting and ending position (\pm 1 turn accuracy). Supplied pretension system with pulleys with 9-weight kit, up to 70 cN, adjustable clamp speed, up to 2000 rpm.

Accessories included: magnifying lens, fixed calliper, pretension weights, bobbin holder.

Optional: additional pretension weights (1 N, 1,5 N and 2 N), Code 2531C.104.

Reference standards: ASTM D1422, ASTM D1423, UNI 9067, UNI 9277, UNI 9069, UNI EN ISO 2061, ISO 7211-4, ISO 17202, ISO 2061

Power supply: 1,5 V battery x 6 Weight: 9 kg Dimensions: (L) 1000 x (W) 340 x (H) 220 mm

Twist Lab Semi-automatic twist tester



Electronic Twist Tester to determine twist of single, twisted ("S"/"Z") and Open End yarns.

Three methods available to be selected by the operator:

a) Traditional method: untwisting and retwisting, for single yarns.

b) "Schutz" method: untwisting, retwisting and double countercheck, for OE yarns, worsted and slippery yarns.

c) Direct method: untwisting, for plied spun yarns, threads and multi-filament yarns.

Adjustable test length (distance between clamps) from 1 to 50 cm (0.39-19.6 inches).

Built-in digital tachometer and optical sensor with led showing correct zero starting and ending position. (±1 turn of accuracy). Very accurate elongation index with built-in mechanical clamp.

Pretension system with pulleys with 9-weight kit, up to 70 cN. Adjustable clamp speed, up to 2000 rpm.

Endowed with two serial ports, for connection to PC (software included) and to printer (optional).

Accessories included: magnifying lens, fixed calliper, pretension weights, bobbin holder, software and cable.

Optional: printer, additional pretension weights (1 N, 1,5 N and 2 N), **Code 2531C.104**.

Reference standards: ASTM D1422, ASTM D1423, UNI 9067, UNI 9277, UNI 9069, UNI EN ISO 2061, ISO 7211-4, ISO 17202, ISO 2061

Power supply: 115 Vac or 230 Vac, 50/60 Hz Weight: 11,5 kg Dimensions: (L) 1060 x (W) 300 x (H) 220 mm 2531C

YARNS









Computerised instrument for automatic measurement of the friction coefficient of yarns.

Recommended for wax selection and control of waxing process (wax distribution on the yarn and wax duration).

It enables automatic execution of multiple tests on a single package of yarn without operator attendance.

Continuous control of test parameters affecting the friction coefficient, such as input pretension (value and tolerance) and yarn speed, which can be adjusted by the operator up to 50 cN and from 50 to 300 m/min.

Very accurate reading of the input and output tension by means of two electronic tensionmeter heads.

Pre-selection of the yarn length to be measured.

Pre-selection of the yarn length between two consecutive measurements as an alternative to random testing.

Software (Windows compatible) for data saving and elaboration. Print-out listing test results, statistics, graphical representation of single test coefficient of friction and average value.

Optional:

Pc, printer

Attrifil III (**Code 233C**) can be connected with the Auto Cop Changer (**Code 299A**) to automatically perform tests on 24 different bobbins.

Along with the Auto Cop Changer (ACC, **Code 299A**), a creel is required (**Code 3102**).

Reference standards: ASTM D3108

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Air supply: 6 bar Weight: 30 kg Dimensions: (L) 470 x (W) 330 x (H) 310 mm



Modular strength tester **automatically** performing tensile tests and hysteresis cycles on yarns; it semi-automatically executes traction, compression, tearing tests on fabrics, covering adhesion tests, tensile test on yarn and hanks (LEA test).

The exclusive Auto Cop Changer system (ACC, **Code 299A**) enables to test automatically up to 24 different yarns according to the parameters set in the PC by the operator.

Automatic single column strength tester, with adjustable speed up to 5000 mm/min, and with movement resulting from a ball bearing screw; it is controlled by a software, which runs all the functioning phases.

Thanks to the specific modular software, Autodyn II Plus allows to perform tests in compliance with the main international standards, or according to parameters set by the operator, which can be saved for future needs.

Autodyn II Plus can fit different load cells - easy to change - with maximum capacity of 1000 N, and a huge range of pneumatic and mechanical clamps.

Modular design specifically conceived for textile industries requiring both automatic and semi-automatic testing of yarns, hanks, fabrics, covering cloths and seams.

Available also an automatic version with one position, **Code 2514** (see "Fabrics" section for more details).



Optional: PC, printer, LCD monitor	
interchangeable load cells of 20 N	Code 2514A.276
interchangeable load cells of 100 N	Code 2514A.993
interchangeable load cells of 1000 N	Code 2514A.282
Mini autoclamps for low tenacity yarns	Code 2514A.918
Maxi autoclamps for high tenacity yarns (also sewing threads)	Code 2514A.930
LEA clamps for hanks (manual mode)	Code 2514A.990
Scott 100 clamps for yarns and industrial small ropes (mechanical)	Code 2514A.995
Mobile vertical creel	Code 3102

Other clamps for yarns and fabrics are available on request.

Reference standards: ISO, DIN, ASTM, BS, UNI, M&S

Power supply: 115 Vac or 230 Vac, 50/60 Hz Air supply: 6 bar Weight: 118 kg Autodyn dimensions: (L) 600 x (W) 660 x (H) 1630 mm



Maximum elongation

YARNS



Example of Hysteresis cycle test



Available Load Cells:

Load cell	Load Accuracy [cN]	Resolution [cN]
20 N	0,4	0.0002
100 N	2	0.001
500 N	10	0.005
1000 N	20	0.01
5000 N	100	0.05

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 75 kg

Dimensions: (L) 480 x (W) 370 x (H) 1415 mm

Tenso-Lab 4 is the latest generation of the well-known Tenso-Lab semi-automatic tensile tester. The new model is distinguished by:

New hardware:

high sensibility and robustness (can be used to test both fibres and high tenacity fabrics), direct-drive ball bearing screw, low speed operation available, extended capacity to 5000N, ...

New components:

improved load cells performances (higher accuracy level and new capacity load cell added), guick load cell & clamps/jaws exchange, ...

New open software:

more intuitive and easy to operate, SQL database and standard Ethernet machine connection to data export, no restriction on testing routines (can be created by the enduser, no special skills needed)

Features:

Built according to the CRE (Constant Rate of Extension) testing principle

Belt free, direct-drive ball bearing screw

Automatic pretension and automatic load cell and clamp recognition

Top quality load cells (manufactured by HBM – Germany), accuracy class $\pm 0.02\%$

High resolution sensor integrated into the motor ensures accurate clamp position (less than 0,02 mm)

possibility to perform tests at extremely low speed

Automatic reset of force values when load cell/clamps are changed

High resolution of acquired data

High return speed (1800 mm/min)

Quick load cell exchange (only 10 sec. compared to 2 min. of other models)

Advanced alarm system prevents accidents; safety clamp movement system

The Software is modern, flexible and easy to use, it includes a series of standard testing routines. New testing routines can be created by the enduser, no special skills needed

Reference standards: UNI, UNI EN, UNI EN ISO, ISO, ASTM, M&S Officially approved by Marks & Spencer.

ISO 17025 Calibration Certificate (Accredia - ILAC) available on demand.

Available a variety of interchangeable mechanical and pneumatic clamps for yarns, such as:

mechanical clamps for standard yarns	Code	2510.994
Scott 100 clamps for yarns and industrial small ropes (mechanical)	Code	2510.995
with pneumatic clamps for slippery, delicate or high elasticity yarns for pneumatic clamps,		
the foot switch is required	Code	2510.300
Silent Compressor (available on request)	Code	3390
LEA clamps for hanks (manual mode)	Code	2510.990

Other clamps for yarns and fabrics are available on request.



Portable electronic strength tester built in accordance with ISO, UNI, ASTM, DIN standards. Endowed with printer and USB port. Conceived to measure strength and elongation of yarns and splices. Compact and light, specifically designed for testing in the production area near the machines (winding, spinning and O.E. frames, for example). Test results can be printed and downloaded by means of a USB memory stick and used for further needs.

Measuring range: force from 0 to 60 N (0-6 kg); elongation from 0.5% to 45% (0-110 mm).

> **** MESDANLAB

18/02/2017 10:47:17

(mm/min): Count unit: Tex

2.530

Cv%

Ran

(CN)

Mat 303

Ran

ELONGATION

Tex]

37

0.30

FORCE

219

Elong

XXXX

3.04

3.81

36.66

100.00

2.480

(%) 3.81

22.83

14.78 35.48

Force

219 cN 261 cN

226 cN

307 cN 228

Mode:Str.Tester Test type: B PROVA

Speed

Ten[cN/

RKM :

STAT.

Min

S

Mean

STAT.

Min

Mean

Nr. 01

Electro-magnetic clamps with automatic closure are supplied with the instrument.

Clamps distance: 250 mm.

Testing speed: adjustable up to 1000 mm/min.

Pretension: automatically adjustable according to the pre-set value.

Output: force and elongation results, statistics (min., average, max. force of elongation, CV%), tenacity.

The "Splicer" mode is ideal for splicers' control on automatic winders, measuring force and elongation of spliced yarns (up to 64 drums/splicers), processing of

statistics for each splicer and for the complete winder: indication of out of tolerance joints for each drum/splicer.

Reference standards: UNI EN ISO 2062, ASTM D2256

Power supply: 115 Vac or 230 Vac, 50/60 Hz Weight: 10 kg Dimensions: (L) 450 x (W) 330 x (H) 140 mm

Optional:

Battery kit with built-in feeder 115 Vac	Code	2553.3244
Battery kit with built-in feeder 230 Vac	Code	2553.3240
Manual clamps for slippery yarns	Code	2550.120
Movable Trolley	Code	2550.150



MT Evenness Tester



For the evenness control of slivers, rovings and yarns made of both natural and synthetic/manmade fibres.

Thanks to the use of capacitive sensors, the instrument can measure, analyse, calculate and display (with related printout) the following data:

mass variation diagram

160 channels spectrograph to analyse the wave length spectrogram CV% and U% of mass variations

AVE% (relative yarn count)

I.P.I. with an indication of thin places, thick places and neps D.R.% (deviation rate %)

C.V.% (L) referred to 4 lengths

Diagram of mass variation both in "inert" and "1/2 inert" way

The instrument is composed of:

measuring frame

Personal computer with monitor and printer

Windows OS software

Technical features:

Count range: from 35 g/m (sliver) to Ne 150 max (yarn) - beyond this range, it is recommended to evaluate from time to time. Sample speed: from 8 to 400 m/min.

160 channels spectrograph

Optional:

24-position Auto Cop Changer (ACC)	Code	299A
H-Sensor, hairiness sensor to evaluate the		
yarn hairiness	Code	2342
Yarn creel up to 24 spindles	Code	3102
UPS for power stability	Code	2341.900

Power supply: 115 up to 230 Vac, 50/60 Hz, single-phase Air supply: 6 bar Weight: 51 kg

Dimensions: (L) 490 x (W) 320 x (H) 730 mm

Graphic and Histogram report



Statistical results and histogram

App. Verbio			01 2.1.9			ummary				Print Qa	10 . 2014/0	2/12/10.13		
MESDAN S.P.A.				S/N :			Milli	ame : mes	dan		Test da	te: 2014/0	2/12 15 13	
Test Code	: 30			Lot N	o. : test co	on rotella origi	naleMach	ine Name	a1/None(1	1				
Count N	ec 30	and the local data		Slot	No: /	A	Open	ator Name	intan .		Bill in Color			
viacenai Sp	eed 400	mmn		EVANU	ating time	2min Jusec	Calo	e of scale	+14 100%			4008.88-	da Auto	
Comment	sample 1	for start	entipes rul				Gam	- e (* m	a r Matoj			- TOUTS MID	oe Moto	
PRIMA	RY		_			This	This	This	This	Thick	Thick	Thick	Thick	Nee
	CV%	11%	AVE	CV02/%	U02/5	-30%	-40%	-50%	-60%	+35%	+50%	+70%	+100%	+140
55	10.00		10000			(/lom)	(/km)	(/km)	(/lom)	(/km)	(/km)	(/km)	(/km)	(/km
1/1	13.58	10.71	102.63	3.52	2.79	1194.60	78.91	1.00	0.00	897.95	52.94	1.00	0.00	689.1
1/2	13.70	10.93	100 64	3.71	3.00	1350.41	115 86	3.00	0.00	920 92	66.92	1.00	1.00	717.1
1/3	13.79	10.89	102.38	4.00	3.16	1270.51	90.89	0.00	0.00	926.91	67.92	1.00	1.00	653.2
1/4	13.05	10.39	99.41	3.38	2.69	1079.73	66.92	0.00	0.00	680.20	41.95	1.00	1.00	700.1
1/5	12.96	10.18	103.36	3.39	2.72	993.84	67.93	0.00	0.00	650.24	33.96	1.00	1.00	589.3
Mean	13.42	10.62	101.73	3.60	2.87	1177.82	\$2.10	0.80	0.00	815.24	52.74	1.00	0.80	669.8
Min	12.96	10.18	99.41	3.38	2.69	993.84	57.93	0.00	0.00	650.24	33.96	1.00	0.00	589.3
Max	13.79	10.93	103.36	4.00	3.16	1350.41	115.86	3.00	0.00	926.91	67.92	1.00	1.00	717.1
Range	0.83	0.74	3.94	0.62	0.47	356.58	57.93	3.00	0.00	276.67	33.96	0.00	1.00	127.8
\$0	0.38	0.32	1.65	0.26	0.20	143.29	22.59	1.30	0.00	137.79	15.01	0.00	0.45	50.7
CV6%	2.86	3.05	1.62	7.26	6.96	12.17	27.52	162.98	0.00	16.90	28.45	0.00	55.90	7.57
Q95%	0.44	0.37	1.89	0.30	0.23	164,76	25.98	1.50	0.00	158.42	17.25	0.00	0.51	58.3
SPECTR	OGRAM	(MEAN	ŋ											
tom	2 3	5 7	10cm	20 30	10 70	1m 2	3	5 7	10m 20	30 5	0 70 10	0m 200	300 50	0 700
1 cm	11		TOOM	20 20	10 70	10 2	11		10m 20	10	0 70 10	0m 200	200 84	

Planofil Yarn conical table

Electrical instrument to assess yarn regularity. Endowed with electronic speed adjustment.

Equipped with 2 black anodised aluminium trapezoidal tables (dimensions: $255 \times 600 \times 155$ mm).

For very coarse and bulky woollen and blended yarns, a particular model is available, PLANOFIL PLUS (**Code 2520.290**), equipped with a set of special pulleys for a wider separation of coils.

Two Black tables are supplied with Planofil.

Optional:

Black table Code 2520.580

White table Code 2520.590

Reference standards: ASTM D2255 (for regular cotton yarns)

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 24 kg

Dimensions: (L) 910 x (W) 330 x (H) 530 mm



Optional KIT "TWO" 2520.600

Thanks to the optional Kit "Two" - to be combined with Planofil (**Code 2520**) - it is possible to wind at the same time on the same table two yarns with the same count, enabling a quicker preparation of the table (50% time saving) and a better and immediate visual comparison between the two wound yarns.

Optional:

With Kit "Two" it is necessary to use particular trapezoidal tables:

Black table Code 2520.610*

White table Code 2520.620

* Two black tables are supplied with Kit "Two"

Reference standards: ASTM D2255 (for regular cotton yarns)



ASTM yarn standards

Available in the following count ranges:

Ne 1-12	Code	2520.630
Ne 12-24	Code	2520.631
Ne 24-36	Code	2520.632
Ne 36-50	Code	2520.633
Ne 50-75	Code	2520.634
Ne 75-135	Code	2520.635

Reference standards: ASTM D2255 Dimensions: (L) 635 x (W) 100 x (H) 380 mm





"Standard" Yarn Sample Winder

Suitable for any type of card (320 mm max. length, 95 mm width) and yarn count.

Automatic forward winding movement, and manual reverse winding movement.

Up to 12 different yarn colours can be wound simultaneously.

Width of winding can be predetermined.

Equipped with adjustable yarn pre-tensioner.

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 46 kg Dimensions: (L) 700 x (W) 500 x (H) 450 mm



"Special" Yarn Sample Winder

171A

Special high accuracy model with micrometric winding feed.

Particularly suitable for high production of coloured sample cards, especially medium-fine yarns, such as sewing threads.

Fully automatic forward and reverse winding movement, preselectable through the built-in PLC programmer.

Adjustable spacing, automatic stop.

Maximum winding speed: 1000 turns/min.

Up to 12 different colours can be wound simultaneously. Suitable for any card type (320 mm max. length, 95 mm max. width).

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 75 kg Dimensions: (L) 800 x (W) 450 x (H) 560 mm

Scirocco Automatic regain oven

Automatic moisture regain oven designed to measure moisture content and regain percentage in textile materials, according to ISO, ATSM, IWTO, UNI, UNI EN ISO Standards. PC operated.

Quick sample drying (in about 10 min.) by suction cycle. Adjustable drying temperature ranging up to +140°C.

Testing procedure details: the cabinet automatically continues weighing until the sample attains a stable dry mass.

The computer evaluates the difference among consecutive weighings and stops when the difference between 2 consecutive weighings is lower than 0,05%.

It is possible to determine the duration of the first drying cycle as well as the duration of the further 9 cycles.

The basket tare is recorded according to the basket code.

Ambient humidity and temperature values can be entered in order to obtain automatically the correction of the dry mass (for this purpose, the table of correction coefficient is available in the software).

Equipped with PC, electronic balance (2200 g capacity/0,01 g accuracy), colour printer, and LCD monitor.

Printed report of test parameters and final results, such as:

sample code

basket code

date of basket gauging

weight of wet sample

weight of dry sample

dry percentage

Reference standards:

ISO 6741-1, 2, 3, 4, UNI 1335, UNI 9213-1, 2, 3, 4, 5, 6, ASTM D1576, ASTM D2495, IWTO 33-98, IWTO 34-98, UNI EN ISO 2060

Power supply: 230 Vac, or 400 Vac, three-phase, 50/60 Hz, 10kW Weight: 209 kg $\,$

Dimensions: (L) 1000 x (W) 700 x (H) 1230 mm







Example of report:

a caracteristic	part		Lot	lotto		Date	26/01/2014
Parcel	collo		Operator	esam		Time	11:27:00
Aaterial	Wool (worsted)	Standard	B.R.	18 [%]	Condition	ing 105	5 c
Global Elab	orations		P	nalysis Results		E	nv. Cond.
Total Mass	1000.	00 kg	1	lumid Weight	195,64		emperature
Commercial Mass 1056.40 kg		40 kg	I	Dry Weight	175,06	91	20 C
			F	leal Regain Rate	11,700	[%] R	clative Humidity
# Campioni	Modify Data			lumidity	10,475	[2]	60 [%]
Codice Stufa Sample Des	SCIROCCO MESDAN		N	I.M. Corr. Coeff.	5.640	[%]	

Example of printout of Scirocco oven:

final results of a sample in stock to be shipped and invoiced at the official humidity regain rate.

Real Regain Rate at the Dryer Scirocco MesdanLab					
Customer Code	Test		Date 20/02/13	Time 14.38.31	
Test Code	Test				
Stock			Lot	lotto	
Parcel Material	Wool (worsted)		Operator Material R R		18%
Wateria	woor (worsted)		Waterial N.N.		10 /0
Conditioning Temperature	105	°C			
Number of Samples	1				
Humid Weight	402,5	g			
Real Regain Rate	11,517	%			
Humidity	10,328	%			
Dry Weight	360,75	g			
Present Dry Weight	360,93	g			
Corr. Coeff. of Net Mass	5,813	%			
Net Mass	180	kg			
Commercial Mass	190,464	kg			
Testing Machine	SCIROCCO MESDAN				
Testing Conditions	20	°C	Humidity		60%
Sample Description					



Moisture content in fibres and yarns is of paramount importance in both textile trade and final product quality evaluation. Moisture variation can lead to serious quality issues such as "barré" defects, dimensional stability problems, etc.

AQUA-LAB is an innovative instrument for fast and accurate measurement of the moisture regain and moisture content in textile materials.

Its measurement speed allows HIGH VOLUME CONTROL OF MOISTURE throughout every stage of the textile chain increasing consequently the productivity and the efficiency of the process, as well as the final product quality.

The measurement principle of Aqua-Lab is based on an innovative low power resonance technology.

AQUA-LAB calibration algorithm associates the mass-independent microwave moisture values measured by AQUA-LAB with the moisture regain values measured by the drying oven (the only reference instrument for measuring the moisture content of textile fibers). Aqua-Lab absolute value correlation with the regain oven (drying system) makes Aqua-Lab indispensable for commercial transactions, pricing management and QC monitoring.

Specific preset calibrations are available for different textile materials, easily selectable by the operator from the starting menu.

The complete AQUA-LAB, **Code 2450**, is equipped with two sensors: one for fibres (loose fibres, tops, slivers, etc), one for yarn packages (cones, roving cops, etc). However, the system can be supplied equipped with one sensor only:

for fibres, Code 2450A

for yarn packages, Code 2450B

Ideal for Ginners, Top Makers, Spinning Mills, Wool Combers, Yarn Buyers, Dyeing Mills, Textile Laboratories. Main features:

Fast, real-time measurement.

High repeatability and reproducibility of results.

Perfect correlation with oven-drying.

Suitable for any textile fibre such, for example, cotton, linen, wool, cashmere, viscose, silk, acrylic, synthetics as well as blends.

No sample weighing or preliminary preparation of the sample is required.

Non-destructive method, no waste of material.

Simple test execution, which can be performed by unskilled personnel as well.

Results are not influenced by the weight of the sample, by its dimensions, its density and environmental conditions (temperature and humidity).

Very low power consumption.

Easy maintenance: no consumables, no wear.

Ethernet available (connection to central data collection system).

Power supply: 115 up to 230 Vac, 50/60 Hz, single-phase Dimensions and weight:

Main Unit: (L) 200 x (W) 110 x (H) 150 mm, 2.5 kg Yarn package Sensor: (L) 250 x (W) 170 x (H) 85 mm, 2.5 kg Fibre Sensor: (L) 325 x (W) 375 x (H) 430 mm, 17 kg

AQUA-LAB recognition

At the 32nd International Bremen Cotton Conference, the **ITMF** International Committee on Cotton Testing Methods (**ICCTM**) gave full recognition to AQUA-LAB



Libeccio Semi-automatic regain oven 245B

Semi-automatic moisture regain oven to measure moisture content and regain percentage in textile materials according to ISO, ASTM, IWTO and UNI Standards. Quick Sample drying (in about 10 min.) by suction cycle. Adjustable drying temperature ranging up to +140°C. Complete with electronic balance (2.200 g capacity/0,01 g accuracy). Automatic movement of the weighing basket by means of "up and down" button. High precision electronic thermo-regulator.

Reference standards: ISO 6741-1, 2, 3, UNI 1335, UNI 9213-1, 2, 3, 4, 5, 6, ASTM D1576, ASTM D2495, IWTO 33-98, IWTO 34-85, UNI EN ISO 2060, ISO 2060, ISO 6348

Power supply: 230 Vac or 400 Vac, three-phase, 50/60 Hz, 8 kW Weight: 150 kg

Dimensions: (L) 980 x (W) 700 x (H) 1350 mm

Humy Tester III

185C

Digital electronic portable instrument for the instantaneous measurement of the humidity percentage contained in textiles. Reading on LCD display with 17 pre-set reading scales for the most common fibres and blends (other reading scales are available). It can be fitted with interchangeable electrodes suitable for cones, hanks, cotton bales or wool and fabrics. Measuring accuracy: $\pm 1\%$.

Optional (not supplied with the instruments):

electrode for cotton or wool bales (2 pins - 30 cm length)	Code	185.412
electrode for hanks (2 pins - 10 cm length)	Code	185.414
electrode with roller for fabrics	Code	185.416
electrode for bobbins and cones (8 pins - 6 cm length)	Code	185.418
probes for calibration (2 pcs)	Code	185.422
electrode for man-made yarns	Code	185.424
probe for ambient temperature / humidity	Code	185.428
Reference standards: DCS 194 (Decathlor	า)	
Power supply: 9 V battery Weight: 0,4 kg Dimensions: (L) 100 x (W) 40 x (H) 220 r	าฑ	

Hardness Tester

For checking packages and cops hardness Measuring scale 0-100° Shore. Equipped with pressure control device.	i.	
Available in the following models:		
HP 2.5 for synthetic filaments	Code	255A
HP 5 for cotton and wool yarns	Code	255B
To check beam hardness, the following flat base	models are ava	ailable:
HP 2.5 F for synthetic filament	Code	255E
HP 5 F for cotton/wool yarns	Code	255D
To check rubber, the following model is available	ailable:	
HP SA, scale: 0-100° Shore A	Code	255F
Weight: 0,30 kg		









High performance computerised system conceived for the analysis of fibres, yarns, fabrics, knits, non-wovens, spinnerets etc. Equipment suitable to perform in a fast and easy way the fineness analysis of single fibres, identify the different type of fibres contained in a blend and analyse the composition percentage. Ideal to check the features of purchased material, analyse yarn structure and detect possible defects. Suitable to measure the count (dtex/ den) of yarns and round section filaments; to analyse quality of Lycra filaments into the yarn, the compactness of non-woven fabrics, yarn and fibre sections; to measure section surfaces and perimeters;

to analyse mechanical parts (i.e. needle points, spinnerets, etc); to reduce warp and weft density of fabrics to a cm or a inch; to process, store and print the produced measurements and the minimum, medium and maximum values, CV% and distribution graphs.

The system is composed of:

LEICA Biological Microscope: magnification on screen from 195X to 2830X with slide movement device with micrometric regulation, polarising light, for fibres and yarns analysis, etc.

LEICA Stereo Microscope with magnification on screen from 16X to 189X, with illuminated base, for the analysis of fabrics, yarns and mechanical parts like travellers, needles and spinnerets.

Led Ring Light Illuminator.

PC complete with LCD monitor and photographic quality printer.

Professional digital colour camera, 1/2.33", CMOS, 16.0 Mpixel, USB 3.0, to acquire images from microscope.

Software for the image acquisition, the production of measurements and comments on the stored images and measurement directly on the live images, the statistic analysis of the acquired measurements.

Fibre Microscope Kit (Code 250.325) for the microscopic analysis (fibres, yarns and fabrics); instructions for sample's preparation.

Optional:

Optical fibre illumination device, (for both biological and stereo microscope), for a perfect illumination of a sample from different adjustable angles.	Code	250.318
63X LENS (for biological microscope): it enables a 2830X on screen magnification.	Code	250.336
C-STEP CONNECTOR WITH 0.5X LENS (for biological Microscope). The installation of this connector allows to halve the magni- fication on screen and double the sample field of vision.	Code	250.338
C-STEP CONNECTOR WITH 0.5X LENS (for Stereo Microscope). The installation of this connector allows to halve the magnification on screen and double the sample field of vision.	Code	250.334
TRINOCULAR KIT (for Stereo Microscope) to display the sample image either on the PC monitor or in the oculars	Code	250 340
Set of 50 slides	Code	191 50
Set of 200 slide covers	Code	191.50
Bottle of oil immersion	Code	191.52
Pack of paper for printer	Code	250 18
		200.10
Set of cartridges for printer.	Code	250.322

Reference standards: ISO 137, UNI EN 12751, UNI 5423, UNI ISO 1130, ASTM D629, ASTM D2130, ASTM D276, AATCC 20, IWTO 8, IWS TM24, NIKE (section H, fiber content testing requirements)

Power supply: 100 up to 240 Vac, 50/60 Hz Weight: 53 kg Dimensions: (L) 1080 x (W) 700 x (H) 700 mm
Examples of the most typical applications of Video Analyser:



Dye Scanner Yarn-knit (Dye) uniformity





Detail of yarn pretensioner

List of available cylinders

Code**	no of needles	Needle gauge	Indicative nominal count range *	
294E 1320	320	75	Dtex	10-100
294E 1260	260	70	Dtex	30-150
294E 1240	240	48	Dtex	70-300
294E 1220	220	48	Dtex	100-400
294E 1140	140	36	Dtex	200-1000
294E 1112	112	24	Dtex	400-2000

Laboratory knitting machine for the automatic production of tubular knitted fabrics for checking dyeing uniformity and dye affinity, for assessment among different yarn bobbins. Suitable for synthetic, natural and artificial yarns.

Equipped with Auto Cop Changer (ACC) with 24 or 36 bobbins, electronic yarn feeder, electronic pretension device, automatic bobbin change marking device, 36-yarn conveyor.

Main technical features:

Ergonomic panel with electronic counter, speed potentiometer and led indicators of machine functions.

Rotation speed of cylinder adjustable from 0 to 450 rpm by means of an electronic potentiometer.

High productivity: 1000-1200 samples (2,5 cm length) in about 10 hours.

Electronic counter to set sample length and number of samples.

Automatic oiling device for the cylinder.

Endowed with fabric fineness adjustment mechanism.

Interchangeable Cylinder \emptyset 3, 3/4" diameter suitable for a wide range of yarns.

Electronic automatic yarn pre-tensioner (0,1 cN accuracy) enabling constant and precise tension during operation.

Electronic device marking the knitted fabric when bobbin is changed.

Equipped with Auto Cop Changer (ACC) with built-in mechanical knotter.

Yarn feeder enabling change of cop while machine is running a test. Yarn alignment device.

Two models available:

24-bobbin Auto Cop Changer (ACC); Code 2940B

36-bobbin ACC 36 yarns rack conveyor to

the ACC (to speed-up creel change operation) Code 2940A

Power supply: 400 V, 50 Hz, three-phase + N, 1,9 kW Air supply: 6 bar Weight: 200 kg

Dimensions: (L) 1500 x (W) 4000 x (H) 1750 mm

In order to check and reveal dyeing uniformity, the tubular knitted fabrics produced by the DYE SCANNER have consequently to be dyed. GIOTTO HT 9000 is the ideal equipment for this purpose. In fact, it can dye up to about 300 g of tubular knitted fabric samples, and - thanks to its exclusive and innovative built-in automatic dosing system - GIOTTO HT 9000 can wash, dye, rinse, and - if necessary - soap the samples.

High-pressure bath at a temperature of +135 °C, therefore ideal for dyeing of polyester fabric samples. Equipped with automatic dosing system, this instrument is also suitable for dyeing with reactive dyestuffs.

* Cylinder capacity should be confirmed by yarn testing, as cylinder selection is affected by yarn count, composition and friction.

** Cylinders with different capacity are available on request.

Mini Spinning

A real spinning mill in miniature, to produce small lots of short and long staple yarn.

Ideal for:

textile institutes and research centres spinning mills of blends spinning mills of woollen yarn

Laboratory Carding Machine 337A

Miniature carding machine designed to produce a homogenous sample of fibres of different colour and/or nature. It can process both short and long fibres. The machine can deliver either web, or sliver, by means of the Coiler, Code 337A.6, available as optional. Self-cleaning system, to avoid dirtying of the sample. Delivery speed: 10-15 m/min. Safety devices: emergency stop, switch on moving panels, Plexiglas protective cover. Average production: 4 kg/hour Working width: 500 mm (19.69") Web max. width: 480 mm (18.90")

Power supply: 230 Vac, or 400 Vac, three-phase, 50/60 Hz Weight: 640 kg Dimensions: (L) 1910 x (W) 850 x (H) 1440 mm

Coiler

337A.6

Web Condenser, specifically designed for the Laboratory Carding Machine, Code 337A, to transform the carded web into sliver, and collect it into a proper can for further processing.

Stiro Roving Lab Miniature draw frame

Miniature draw frame to double and draw in form of an even homogenous sliver the web coming from the Laboratory Carding Machine.

Suitable for short and long fibres.

Stiro Roving Lab is complete with a device to transform the sliver into a roving and wind it on a spool.

Adjustable draw from 2x up to 6x.

Adjustable distance between drawing rollers. Adjustable drawing speed and pressure.

Optional: Flyer Twisting Unit (Code 3371.2)

Power supply: 230 Vac, 50/60Hz Weight: 180 kg Dimensions: (L) 1600 x (W) 680 x (H) 1280 mm



Detail of Stiro Roving Lab

Flyer Twisting Unit







Ring Lab Mini ring spinning

Mini spinning frame with 6 spindles designed for spinning trials of cotton, woollen, synthetic and blended yarns. Special model suitable to process slivers or rovings produced by Stiro Roving Lab. Endowed with 5 rollers, to draw the sliver up to 400X. Spinning capacity: from Ne 8 up to Ne 80.

Electronic setting of delivery speed, twist, draw and twist direction.

Technical details:

variable speed drive: from 3500 to 25000 rpm Ring diameter: 45 mm; tube length: 240 mm Spindle speed: up to 18000 rpm Special creel for sliver supply included.

Optional kit for core-yarn available on request. Digital control panel to show in real time: rpm – tpm – break draft - total draft - delivery speed in m/min - etc.

Power supply: 115 Vac or 230 Vac, 50 Hz or 60 Hz Weight: 335 kg Dimensions: (L) 1000 x (W) 700 x (H) 2100 mm

Wind Lab

3374

3108A

Manual winder with two heads. Adjustable winding speed: from 300 up to 1000 m/min. Winding traverse: 6" (152 mm); conicity: 5° 57'.

Power supply: 230 Vac, 50/60 Hz Weight: 71 kg Dimensions: (L) 700 x (W) 500 x (H) 1250 mm

Mini Assembly Lab Mini assembly winder

Single head assembly winder to produce cylindrical cones to be twisted.

Endowed with electronic panel to set parameters, such as length meter and automatic stop.

Winding speed: from 200 up to 1200 m/min.

Power supply: 230 Vac, 50/60 Hz Weight: 100 kg Dimensions: (L) 900 x (W) 900 x (H) 1300 mm

Twister Lab Two for one lab twister 3373

Single head two-for-one twisting machine to produce cones of plied yarns in the laboratory.

Endowed with touch screen display to set winding parameters: spindle speed, tpm., winding angle, "S"/"Z" direction. Display of quantity of processed yarn in meters.

Spindle type 202B with adjustable speed from 5000 up to 13000 rpm.

Twisting collecting from 8 to 100 m/min. 6" winding traverse and 4° 20' conicity.

Power supply: 230 Vac, 50/60 Hz Air supply: 6 bar hose ø 6 mm Weight: 130 kg Dimensions: (L) 470 x (W) 650 x (H) 1450 mm

Lab Knitter Yarn-knit (Dye) uniformity 294E

High precision single cylinder laboratory knitting machine for the production of tubular knitted fabric for checking dyeing uniformity and evaluate dye affinity.

Interchangeable cylinder, 3,3/4" diameter, suitable for a wide range of yarns (to be selected from the available ones listed in the attached chart).

Endowed with fabric fineness regulation mechanism.

Automatic oiling device.

Ergonomic control panel complete with:

electronic yarn length meter;

variable speed regulation by means of a potentiometer;

Led indicators monitoring machine's functions.

Optional:

electronic tensioner	Code	294E.1100
foot switch	Code	294E.80

Power supply: 400 Vac, 50/60 Hz, three-phase + N, 1.1 kW, or 230 Vac, 50/60 Hz, single-phase, or 230 Vac, 50/60 Hz, three-phase Weight: 130 kg

Dimensions: (L) 450 x (W) 850 x (H) 1750 mm

List of available cylinders

Code**	nr of needles for filaments	Needle gauge	Indicative count rangefor filaments		Indicative count rangefor spun yarn*
294E 1320	320	75	Dtex	10-100	Ne 80-120
294E 1260	260	70	Dtex	30-150	Ne 60-80
294E 1240	240	48	Dtex	70-300	Ne 40-60
294E 1220	220	48	Dtex	100-400	Ne 20-40
294E 1140	140	36	Dtex	200-1000	Ne 12-20
294E 1112	112	24	Dtex	400-2000	Ne 8-12

* Cylinder capacity should be confirmed by yarn testing, as cylinder selection is affected by yarn count, composition and friction.

** Cylinders with different capacity are available on request.





Polar Evo Wind-Lab 3374D

Fully automatic SAVIO POLAR EVO single-head winder equipped with:

touch screen control panel with PC

a wide choice of different interchangeable MESDAN yarn splicers LOEPFE electronic yarn clearer

automatic carousel feeding magazine

waxing device, tension control, yarn length measuring device ...

Ideal for:

didactic purposes in textile schools, universities, etc.

waste yarn recovery, especially in weaving (yarn leftovers during warping)

as a complementary machine to the "Mini Spinning" line R&D labs (for research on winding, yarn clearing, waxing, splicing, etc.)

All parameters of the winding process are computer controlled: yarn quality

package quality

production quality

alarm monitoring system

All moving parts are driven by individual independent driving motors (upper package and lower bobbin suction, splicer, yarn tensioner).

Power supply: to be defined at order Installed power: 4 kW - Electrical consumption: 2kW Compressed air consumption: 8 normal litres Weight: 340 kg Dimensions: (L) 1000 x (P) 1100 x (H) 1900 mm

Mini Spinning Layout



RECOMMENDED CONFIGURATIONS

Basic (for spinning mills): Single yarns assessment: 1+2+3+4 Plied yarns assessment: 1+2+3+6+7+4 **Top** (for research centres and institutes): With manual winder: 1+2+3+5+6+7+4AWith auomatic winder: 1+2+3+5A+6+7+4A



FABRICS

p 44 p 45 p 46 p 47	Tenso-Lab 4 / Tensile strength tester Tenso-Lab 5000 / Tensile strength tester Autodyn II / Automatic tensile strength tester Available clamps for Tenso-Lab and Autodyn	Code Code Code	2512E 2515 2514
p 49 p 49 p 49 p 50 p 51 p 52 p 52 p 53 p 53 p 53 p 54 p 556 p 57 p 57	Crease Recovery Tester Wrinkle Recovery Tester Martindale Burstmatic / Bursting tester Spray Rating Tester ICI Pilling & Snagging Tester 4 positions Digital electric-hydraulic Bursting Tester Elmendorf Pneumatic Fabric Stiffness Tester Thickness-Lab / Thickness tester Water Proof Air Tronic Plus Elmatic / Elmendorf tearing tester MacroLab / Yarn-fabric analysis Portable Microscope Pick Counters	Code Code Code Code Code Code Code Code	3109 3110 320A 2568 338E 333A 279G 338D 275A 3396 1880 3241C 3240C-E-F 275D 250F 2604
p 57 p 57 p 57 p 57 p 58 p 58 p 58 p 59 p 60 p 61 p 62 p 633 p 634 p 634 p 633 p 634	Microscope for fabrics Circular Sample Cutter Electronic balance per m ² Crock Meter / Rubbing fastness Electric Crock Meter / Rubbing fastness Forced Ventilation Conditioning Oven Sample Press Lab Hoff-Lab Press Scorch Fastness / Sublimation tester Perspirometer Incubator Sun Lab / Light fastness Xenon Lab / Light fastness Wascator Tumble Dryer Dry Cleaning Machine Top Loading Home Tumble Dryer Autowash II / Wash-Dry colour fastness	Code Code Code Code Code Code Code Code	191G 175B 165.664 2540 198B 251G 1750A 3370B 312A 257A 251L 325A 310B 3111 310F 310H 3111B 311L
p 64 p 64 p 64	Grey Scales Blue Scale Standard Adjacent Fabrics	Code	325.2
p 64 p 64 p 65 p 65 p 65 p 65	Multifibre DW 010 Multifibre TV AATCC/ISO Crease Appearance Replicas AATCC/ISO Seam Smoothness Appearance Replicas Soap Powder	Code Code Code Code Code Code	257.424 257.426 310.94 310.96 310.74 310.10
p 65 p 66 p 66 p 67 p 67 p 67 p 67 p 67 p 69 p 69 p 69 p 70 p 71 p 72 p 72	ECE/IEC Reference Detergent Vapour Permeability Tester Water Vapour Test Static Lab Glove Cut Tester Linear Cut Resistance Tester Impact Abrasion Lab ISO Flammability Lab 45° Flammability Tester Horizontal Flammability Tester Vertical Flammability Tester Sweating Guarded Hot Plate Integrated Sweating Guarded Hot Plate System ANDI Thermal Manikin Automotive Thermal Comfort Daviag Pato Tester DPT201	Code Code Code Code Code Code Code Code	3122 3395 291B 3394A 3394B 2563 3392E 3392C 3392C 3392D 3392G 3123 3123B

p 72 Drying Rate Tester DRT201



Tenso-Lab 4 Tensile strength tester



Example of Hysteresis cycle test



Available Load Cells:

Load cell	Load Accuracy [cN]	Resolution [cN]
20 N	0,4	0.0002
100 N	2	0.001
500 N	10	0.005
1000 N	20	0.01
5000 N	100	0.05

Tenso-Lab 4 is the latest generation of the well-known Tenso-Lab semi-automatic tensile tester. The new model is distinguished by:

New hardware:

high sensibility and robustness (can be used to test both fibres and high tenacity fabrics), direct-drive ball bearing screw, low speed operation available, extended capacity to 5000N, ...

New components:

improved load cells performances (higher accuracy level and new capacity load cell added), quick load cell & clamps/jaws exchange, ...

New open software:

more intuitive and easy to operate, SQL database and standard Ethernet machine connection to data export, no restriction on testing routines (can be created by the enduser, no special skills needed)

Features:

Built according to the CRE (Constant Rate of Extension) testing

principle

Belt free, direct-drive ball bearing screw

Automatic pretension and automatic load cell and clamp recognition

Top quality load cells (manufactured by HBM – Germany), accuracy class \pm 0,02%

High resolution sensor integrated into the motor ensures accurate clamp position (less than 0,02 mm) $\,$

Possibility to perform tests at extremely low speed

Automatic reset of force values when load cell/clamps are changed

High resolution of acquired data

High return speed (1800 mm/min)

Quick load cell exchange (only 10 sec. compared to 2 min. of other models)

Advanced alarm system prevents accidents; safety clamp movement system

The Software is modern, flexible and easy to use, it includes a series of standard testing routines. New testing routines can be created by the enduser, no special skills needed

Reference Standards: ISO, UNI, UNI EN, UNI EN ISO, ASTM, M&S, NEXT, JIS.

Officially approved by Marks & Spencer.

ISO 17025 Calibration Certificate (Accredia - ILAC) available on demand.

A variety of interchangeable mechanical and pneumatic clamps for yarns and fabrics is available.

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 75 kg $\,$

Dimensions: (L) 480 x (W) 370 x (H) 1415 mm



Two-column universal electronic strength tester (CRE) developed to meet the high quality testing requirements of universities, research institutes and leading companies. With a maximum capacity of 5000 kg (50 kN), it is suitable to test also technical textiles, geo-textiles, non-woven and industrial textiles in general. Twin ball screws ensure the smooth movement of the crossbar, sliding between two reinforced guide columns that prevent any deformation of the framework. Available a 1000 kg (10 kN) version, **Code 2516**.

Working speed: from 0.5 to 500 mm/min

Maximum travel of the crossbar: 1200 mm (without clamps)

Inner distance between the columns: 400 mm

Developed to be used with a wide range of easily interchangeable load cells and clamps, both mechanical and pneumatic.

Tenso-Lab 5000 is PC controlled. Thanks to the different operating softwares available, it can perform traction, compression, tearing, delamination, adhesion, seam slippage tests and hysteresis cycles, according to specific international standards.

A Mechanical Exstension Device is available as optional, for a further check of elongation on very rigid samples with low intrinsic elongation. Available load cells:

maximum capacity 2 daN (kg)	Code	2515.276
maximum capacity 10 daN (kg)	Code	2515.280
maximum capacity 100 daN (kg)	Code	2515.282
maximum capacity 500 daN (kg)	Code	2515.283
maximum capacity 1000 daN (kg)	Code	2515.284
maximum capacity 5000 daN (kg)	Code	2515.288
precision of load cells: 0,05%		

Several types of clamps, both mechanical and pneumatic, are available according to the type of standards. Pc available on request.

Reference Standards: ISO, UNI, UNI EN, UNI EN ISO, ASTM, M&S NEXT, JIS.

Officially approved by Marks & Spencer.

ISO 17025 Calibration Certificate (Accredia - ILAC) available on demand.

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase, 300 W Weight: 322 kg Dimensions: (L) 900 x (W) 600 x (H) 1900 mm



Modular strength tester designed to execute automatically tensile tests and hysteresis cycles on yarns; it semi-automatically executes traction, compression, tearing test on fabrics, covering adhesion tests, tensile test on yarns and hanks (lea test).

Automatic single column strength tester with movement resulting from a ball bearing screw; it is controlled by a software which runs all the functioning phases. Thanks to the specific modular software, Autodyn II allows performing tests in compliance with the main international standards or according to parameters set by the operator which can be saved for future need.

Autodyn II can fit different load cells easy to be changed with maximum capacity of 1000N, and a wide range of pneumatic and mechanical clamps.

Working speed: from 10 to 5000 mm/min.

Modular design specifically conceived for textile industries requiring both automatic and semi-automatic testing of yarns, hanks, fabrics, covering cloths and seams.



Available also in the 24-position automatic version - code 2514A

Optional:

PC, printer

interchangeable load cells of 20 N, 100 N, 1000 N

wide range of mechanical and pneumatic grips for yarns, hanks, and fabrics

Reference standards: ISO, DIN, ASTM, BS, UNI, M&S standards

Power supply: 115 Vac or 230 Vac, 50/60 Hz, 300 W Air supply: 6 bar Weight: 85 kg Dimensions: (L) 610 x (W) 610 x (H) 1340 mm



Available clamps for Tenso-Lab and Autodyn

continued on next page ----->



Pneumatic clamps for delicate yarns such as POY, Lycra, cotton and worsted yarns (20N max capacity), Code 2510.978



Pneumatic clamps for standard yarns and sewing threads (50N maximum capacity), **Code 2510.982**



Mechanical clamps for normal yarns (30N capacity), Code 2510.994



Clamps for yarns (high tenacity) with conical introducer, Code 2510.980



Mechanical clamps for high tenacity yarns: - Scott type 100 - Code 2510.995 - Scott type 300 - Code 2510.996



LEA clamps for hanks, Code 2510.990



Mini clamps for yarns up to 20N (for Autodyn only), Code 2513.918. Maxi clamps for yarns up to 50N (for Autodyn only), Code 2513.930



Self-tightening high tenacity clamps for ribbons 100mm wide, **Code 2510.920** (for Tenso-Lab 1000-5000 only)



Self-tightening high tenacity clamps for ropes (for Tenso-Lab 1000-5000 only), Code 2515.988

Available clamps for Tenso-Lab and Autodyn



Pneumatic maxi clamps with rubber jaws, 100mm wide, Code 2510.130 for high tenacity and heavy fabrics (for Tenso-Lab 1000-5000 only). Pneumatic standard clamps with rubber jaws, 100mm wide, Code 2510.844 for light fabrics.



Mechanical clamps with rubber jaws, 100mm wide, Code 2510.846



Mechanical clamps for non-woven, 200 mm wide, with rubber jaws Code 2510.142. Also available for geotextiles.



- rubber covered jaws 100mm - "grab"/rubber jaws 25x25mm
- "grab" jaws 25x25mm

Special testing kit, to ensure that zips are appropriately applied, Code 194E.28



Tool for perforation test of non-wovens in compliance with UNI and ISO Standards (for Tenso-Lab1000-5000 only) CBR Type, Code 2510.690



- knurled jaws 100mm

Tool for perforation test of non-wovens, Persoz type, Code 2510.800



Perforation testing kit according to En 388 standard, Code 2510.681

Crease Recovery Tester 3109

To determine recovery characteristics of fabrics undergoing a preset pressure for a specific period of time.

Reference standards: ISO 2313, AATCC 66, UNI EN 22313, M&S P22

Weight: 8 kg Dimensions: (L) 250 x (W) 200 x (H) 350 mm



Wrinkle Recovery Tester 3110

To determine fabrics resistance to wrinkling. Equipped with one standard comparative reference photographs, one 0.5 kg weight, one 1 kg weight, one 2 kg weight, and two fixing clamps with support.

Reference standards: AATCC 128, ISO 9867.

Weight: 9,5 kg Dimensions: (L) 150 x (W) 150 x (H) 330 mm



Crimp Tester

320A

To determine crimp on yarns, caused by weaving and knitting processes.

The device is used also to measure with absolute accuracy the length of a yarn section, in order to determine, after weighing, the yarn count.

Reference standards: ISO 7211-3, IWSTM 31, UNI 9276, BS 2863, BS 2865, BS 2866

Weight: 2 kg Dimensions: (L) 1500 x (W) 80 x (H) 40 mm



Martindale



Instrument for the control of abrasion and pilling on almost any kind of woven and knitted fabrics, non-wovens, socks, gloves, natural and artificial leather, both dry and wet samples.

Model with 9 positions with LCD touch screen display, equipped with single and total rotation counter.

3 types of test can be performed: abrasion, pilling, and straightline motion.

Also a 6-position model, Code 2568A, is available on request.

Compulsory Accessories (at least 1 is needed):

Set of 9 sample holders, 38 mm Ø, for ABRASION test (according to UNI EN ISO 12947-1) and PULLING test (according to		
ASTM D4970)	Code 2	568.900
Set of 9 sample holders, 90 mm Ø,for PILLING test (according to UNI EN ISO 12945-2)	Code 2	2568.300
Optional:		
Abradant Fabric (1,6x1m) Backing Foam (pack of 25 pcs) Backing Felt disc, 140 mm Ø (set of 24 pcs)	Code Code Code	314.12 314.32 314.8
(set of 24 pcs)	Code	314.20
Set of photographs (ASTM) SM50 for pilling test on woven fabrics (3x4 pcs)	Code	314.14
Set of photographs (ASTM) SM54 for pilling test on knitted fabrics (3x4 pcs)	Code	314.16
Set of photographs (EMPA 991) for PILLING test of woven fabrics	Code	314.18
Set of photographs (EMPA 992) for PILLING test of knitted fabrics	Code	314.24
Sample cutter 38 mm Ø for ABRASION & PILLING test Sample cutter 90 mm Ø for PILLING test Sample cutter 140 mm Ø for PILLING test ISO 17025 Calibration Certificate (Accredia - IL	Code 2 Code 2 Code 2 AC), on	2560.322 2560.324 2560.320 demand.

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 100 kg - Dimensions: (L) 800 x (W) 750 x (H) 410 mm



Officially approved by Marks & Spencer for the following tests: M&S P17 Pilling method P1
M&S P18C Enhanced Pilling
M&S P19 Martindale Abrasion Resistance of Apparel Fabrics
M&S P19A Martindale Abrasion Resistance of Handbags and Belt Fabrics
M&S P19B Martindale Abrasion Resistance of Upholstery
M&S P19C Martindale Abrasion Resistance for Shirtings
M&S P140 Martindale Abrasion Resistance for Shirtings
M&S P140 Martindale Assessment of surface disturbance on fabrics containing micro fibres.
Reference standards:
ABRASION, 38 mm Ø: UNI EN ISO 5470-2, UNI EN ISO 12947, UNI EN 13770, UNI EN ISO 20344, ISO 13520, ISO 17704, UNI EN 13520, ASTM D4966, BS 3424-24 TM 27A, UNI EN ISO 12047 1, 2, 2, 4, WTO, 40, WS, TM 112, VD, 230 211

ISO 12947-1-2-3-4, IWTO 40, IWS TM 112, VDA 230-211, M&S P18C, M&S P19, M&S P19A, M&S P19B, M&S P19C, JIS L1018 6.18.5 meth E, ADIDAS GE 63.

PILLING, 38 mm Ø: IWS TM 196, ASTM D4970, M&S P140, M&S P17.

PILLING, 90 mm Ø: UNI EN ISO 12945-2.



Pneumatic bursting tester to determine the bursting resistance of woven and knitted fabrics, non-wovens and cardboard. The instrument measures the required pressure necessary to burst a tested specimen as well as the specimen extension prior to bursting.

Such test can be carried out in two different ways:

following a specific testing standard already present in the software;

free adjustment of testing parameters.

Besides, Burstmatic can measure the hysteresis (fatigue cycling tests) as well, the specimen behaviour when subject to cycling extensions and relaxations. All settings are freely programmable. Next to this, on a colour wide touch-screen, all the testing parameters, statistic results, graphics showing the dynamic behaviour of the tested fabric either during bursting or cycling tests, can be displayed.

All testing parameters, results and graphics can be stored into the Burstmatic database. The sample distension height is measured by means of laser technology.

Equipped with:

pressure rate auto-check system (no need for calibration foils)

extension height verification system (the use of Johansson gauge blocks is suggested)

a dedicated air inlet for pressure gauge connection (when calibration is needed).

Possible Tests:

Bursting tests using customised settings (freely programmable) Cyclical tests using customised settings

Officially approved by Marks & Spencer (M&S).

Available test areas:

Area	Diameter	Standard
7.3 cm ²	30.5 mm	ISO 13938-2, ASTM D3786, M&S P27, WOOLMARK TM29, NEXT 22
7.8 cm ²	31.5 mm	ASTM D3786, WOOLMARK TM29
10 cm ²	35.7 mm	ISO 13938-2
50 cm ²	79.8 mm	ISO 13938-2, M&S P27, ADIDAS 4.09
100 cm ²	112.8 mm	ISO 13938-2

Measurement range:

Distension	mm	inches	ст	Pressure	bar	kPa	psi
Min	0.1	0.004	0.01	Max pressure	10	1000	145
Max	70.0	2.756	7.00	Resolution	0.001	0.1	0.02
Resolution	0.1	0.004	0.01				



Power Supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Net Weight: 65 kg Dimensions: (L) 370 x (W) 460 x (H) 530 mm



Spray Rating Tester

To determine the surface wetting resistance of fabrics. As optional, standard reference photographs are available (**Code 333.2**).

Reference standards: ISO 4920, AATCC 22, UNI EN 24920, BS 4323, BS 3424 part 26, M&S P23

Weight: 5 kg Dimensions: (L) 280 x (W) 280 x (H) 500 mm

ICI Pilling & Snagging Tester 4 positions

279G

333A



Complete with revolution counter.

Speed setting: 30/60 rpm.

Upon request, 2-position model (Code 279H) can be supplied.

Optional:

special set of nails, to perform snagging test (**Code 279.16**) drum for pilling and snagging test, according to M&S P18 (**Code 279.28**).

Reference standards: UNI EN ISO 12945-1, BS 5811, IWS TM 152, ADIDAS 4.08, ADIDAS 4.25, ICI 444, M&S P18A, M&S P18B

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 69 kg $\,$

Dimensions: (L) 980 x (W) 660 x (H) 800 mm

Digital electric-hydraulic Bursting Tester

338D

To determine fabrics resistance to bursting.

Pressurising device with precision volumetric pump. Safety valve for pressure control. Control lever for test execution, emptying operation and automatic zero setting at release. Control device run by an electric engine at variable speed, with automatic stopwatch to check test duration.

Glycol fluid. Measuring range: from 0 to 50 bar (0 to 5000 kPa). Subdivision: 0,01 bar. Supplied with: 12 membranes of pure para rubber, 12 O-rings, 1 bottle of liquid, 1 wrench for ring dismantling.

Reference standards: UNI EN ISO 2758, ISO 3303, ISO 3689, ISO 2960, ISO 13938-1 (except point 6.1.3), ASTM D3786, Woolmark TM29, UNI EN ISO 13938-1 (except point 6.1.3)

Power supply: 230 Vac, 50 Hz, single-phase Weight: 30 kg Dimensions: (L) 500 x (W) 400 x (H) 400 mm





Elmendorf

275A

Instrument to test tearing resistance of cloths, artificial leather, paper. Interchangeable pendulums having the following capacities can be supplied:

pendulum: 1.600 g	Code	275A.126
pendulum: 3.200 g	Code	275A.128
pendulum: 6.400 g	Code	275A.130

Reference standards: UNI EN ISO 13937-1, UNI EN ISO 4674-2, UNI EN ISO 6383-2, UNI EN 21974, ISO 1974, ASTM D1424, TAPPI T414, NEXT 17, GB/T 3917.1, DIN 53128

Weight: kg 6 (pendulum excluded) Dimensions: (L) 380 x (W) 180 x (H) 380 mm

Pneumatic Fabric Stiffness Tester 3396

For the quick and accurate measurement of fabric stiffness. A plunger of 25,4 mm (1 inch) diameter pushes the fabric through a 38 mm (1,5 inch) diameter hole and the maximum

force is recorded. Selectable measurement units are: 50 kgf, 500N, 100lb.

Reference standards: ASTM D4032

Power supply: 100 up to 230 Vac, 50/60 Hz, + battery Weight: 18 kg

Dimensions: (L) 500 x (W) 500 x (H) 600 mm

Thickness-Lab Thickness tester

1880

Laboratory thickness tester, with digital reading, suitable for woven and knitted fabrics, non-wovens, geotextiles and leather. Reading capacity from 0 to 10 mm, with 0,01 mm accuracy. RS232 port available.

Available models:

in compliance with UNI EN ISO 5084	Codo	1990
Stanuaru (textiles) 20 cm - 0.1 anu 1 kra	Coue	1000
in compliance with UNI EN ISO 9863-1 standard (geotextiles) 25 cm ² - 2 kPa	Code	1880B
in compliance with UNI EN ISO 9073-2 standard (non-woven) 25 cm ² - 0.5 kPa		
and 1 kPa or 10 cm ² - 5 kPa	Code	1880C

Other models for leather, rubber, paper, etc, are also available. Pressure weights and additional plates for each model are available as optional. A version with a measuring range from 0 to 25 mm can also be supplied.

Optional: software for data acquisition and storage Code 1880.2

Power supply: Battery, 3 V, Mod. CR2032, 190 mAh Weight: 23 kg Dimensions: (L) 250 x (W) 310 x (H) 300 mm





Water Proof

Instrument for the analysis of the water permeability of textile materials. It enables to determine the hydrostatic pressure needed for water passage through samples. It also measures the resistance of the samples to water passage at a constant hydrostatic pressure. The tested sample has a surface of 100 cm² and it is fixed with a special air tight system.

Adjustable pressure: 0-9999 mm/H₂O.

"Plus" model (Code 3241D) with adjustable pressure up to 20.000 mm/H₂O is also available.

Supplied complete with "touch screen" for setting and reading of the analysis results.

Software available on request.

Reference standards: EN ISO 20811, DIN 53886, AFNOR G-07057, ISO 811, BS 2823, BS EN 3424 part 26, AATCC 127,UNI 5123, ISO 1420-A

Power supply: 230 Vac, 50/60 Hz, single-phase Weight: 50 kg Dimensions: (L) 540 x (W) 540 x (H) 1700 mm

Air Tronic Plus

3240C-E-F

AIR TRONIC PLUS is a fast and silent electronic instrument to determine the air permeability (meant as speed of the air flow vertically passing through the sample under preset and known testing conditions) of woven, knitted and non-woven fabrics, industrial fabrics for technical use, artificial leather, felt, velvet and paper.

It can calculate also the average pore size of woven fabrics, a unique feature important for the filtration industry, their evaluation and classification.

The air permeability value is expressed in mm/sec. and, thanks to the different testing template areas supplied with the instrument, the air permeability range is extremely wide and goes from a minimum of 1.4 mm/sec up to a maximum of 8056 mm/sec*. The air permeability range of model 3240C (special high capacity model available on demand), goes from a minimum of 180 mm/sec up to a maximum of 55555 mm/sec.

The air permeability value can be also expressed in m/sec. and l/minutes.

AIR TRONIC PLUS is equipped with wheels, as well as a userfriendly touch screen display, a built-in suction unit with cooling system (granting a noise level reduction of about 20-30 dB, in comparison with the "standard models"), and a digital Flux Meter (to perform fast tests).

Optional: Control Lab, Data Management Software, PLC Software Option for average pore size calculation, built-in micro printer, Automatic Pressure Drop Regulator, Seal Fixing Rings, Template Area Adapter.

Reference standards: UNI EN ISO 9237, UNI EN ISO 9073-15, UNI EN ISO 7231, ASTM D737, ASTM D3574 (only model 3240F), JIS L 1096 meth A, NWSP 070.1 RO (15)

Power supply: 230 Vac, 50/60Hz single-phase Weight: 76 kg (model 3240E) - 100 kg (model 3240F) Dimensions: (L) 620 x (P) 620 x (H) 1170 mm

Code	Depressure [10 Pa = 1 mm H ₂ O]		Air flow	Flux meter	Standard Test Area	Optional Test Area
	Pa	mm H₂O	l/h (min-max)	cm²	cm ²	cm ²
3240E	0-2500	0-250	50-5800	Digital (1 unit)	2-5-10-20-50-100	38
3240C	0-2500	0-250	6500-100000	Analogic (1 unit)	5-20-25-50-100	38
3240F*	0-2500	0-250	50-5800	Digital (2 units)	2-5-10-20-50-100	38 / 25 🛛

* Special model, which conforms to ASTM D3574 as well (in addition to all other Standards of models 3240E and 3240C). **Remarks:** bench models are also available on demand (**Code 3240A** and **Code 3240B**).



MESDANLAB



The only ELMENDORF on the market able to automatically perform the following operations:

sample pre-cut

release of the laceration pendulum

reading of the laceration value

blocking of the pendulum

reset of the pendulum into the starting position

Suitable for all kinds of clothes, technical and protective fabrics, as well as for paper, cardboard, natural and artificial leather. Model with a high laceration capacity, ranging from 1600 to 30.000 g. Pendulum complete with additional check weights, supplied as standard with the instrument.

Instrument equipped with alphanumeric keyboard and digital reader for the measurement of the laceration values that can be printed or transferred to a PC through a RS 232 serial port. Instrument fully protected and complying with the strictest EU safety norms.

Reference standards:

Textile - according to: UNI EN ISO 13937-1, UNI EN ISO 4674-2 (coated fabrics), ASTM D1424, ASTM D751 (coated fabrics), UNI EN ISO 1974, M&S P29

Plastic - according to: UNI EN ISO 6383-2-method 360A Paper - according to: TAPPI T414, UNI EN ISO 1974 Officially approved by Marks & Spencer.

Power supply: 115 up to 230 Vac, 50/60 Hz, single-phase Net weight: 66 kg $\,$

Dimensions: (L) 510 x (W) 700 x (H) 630 mm

Pendul	lum	[CN]	+ 1	5000
Specir	hen		:	1
	44	82	.21	сN
START	to	Run	Test	





High performance computerised system conceived for the analysis of fabrics, non-wovens, etc.

Ideal to analyse yarn structures, detect defects, reduce warp and weft density of fabrics to a cm or an inch, and to analyse mechanical parts.

It enables to process, store and print the produced measurements, the related statistics (min., average, max. values, CV%) and the distribution graphs.

The system is composed of:

Stereo Microscope with magnification on screen from 16X to 189X, with illuminated base, for the analysis of fabrics, yarns and mechanical parts like rings, needles and spinnerets.

Led Ring Light Illuminator

PC complete with LCD monitor and photographic quality printer.

Professional digital colour camera, 1/2.33", CMOS, 16.0 Mpixel, USB 3.0, to acquire images from microscope.

Software for the image acquisition (on which measurements and comments can be produced), the measurement on the "live" images directly, and the statistic analysis of the acquired measurements.

Fibre Microscope Kit for the microscopic analysis; instructions for sample's preparation.

Reference standards:

ISO 137, UNI EN 12751, UNI 5423, UNI ISO 1130, ASTM D629, ASTM D2130, ASTM D276, AATCC 20, IWTO 8, IWS TM24, NIKE (section H, fiber content testing requirements)

Optional:

OPTICAL FIBRE ILLUMINATION DEVICE (for a perfect illumination of a sample from different adjustable angles).	Code	250.318
C-STEP CONNECTOR WITH 0.5X LENS The installation of this connector allows to halve the magnification on screen and double the sample field of vision.	Code	250.334
TRINOCULAR KIT To display the sample image either on the PC monitor, or in the oculars.	Code	250.340



Power supply: 100 up to 230 Vac, 50/60 Hz Weight: 50 kg Dimensions: (L) 1600 x (W) 700 x (H) 700 mm

Portable Microscope

Pocket-size microscope with 40X magnification and grazing light.

2604

Pick Counters

Pick counter 10x10 mm and 12X	Code	2601
Pick counter 25x25 mm and 7X	Code	2605





Portable Microscope

Pick Counters

Microscope for fabrics 191G

Stereoscopic microscope with trinocular head frame, particularly indicated for fabric and yarn analysis. Standard magnification from 7X to 45X. Incident and transmitted illumination.

Optional:

A pair of oculars 20X and additional lens 2X, to reach a maximum of 180 enlargements	Code Code	191.66 191.70
Additional lens 0.5X, to reach the standard magnification	Code	191.64
Adaptor for Reflex type camera (T2 ring not supplied)	Code	191.68
Power supply: 230 Vac, 50/60 Hz, single-ph Weight: 7 kg	ase	

Dimensions: (L) 200 x (W) 250 x (H) 400 mm

Circular Sample Cutter 1758

Cutting area: 100 cm².

Cutting depth: 5 mm. Model with 4 blades.

Equipped with one cork support plate and four spare blades.

Reference standards: ISO 3801, UNI EN 12127, ASTM D2646, ASTM D3776, BS 2471, BS 3424, M&S P65, M&S P65A, NEXT 20

Weight: 2 kg Dimensions: (L) 170 x (W) 170 x (H) 150 mm

Electronic balance per m² 165.664

Digital reading electronic balance particularly suitable to check the weight per m² of fabrics and paper, by means of pre-cut round cloth samples with a surface of 100 cm².

The reading capacity of the balance, by using 100 cm^2 round cloth samples, allows the measurement of a maximum weight of the fabric up to 30000 g/m^2 , with an accuracy of 1 g/m^2 . Weighing capacity: 300 g and 0,01 g accuracy. Pan size ø 120 mm.

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 1,9 kg Dimensions: (L) 200 x (W) 200 x (H) 60 mm









Crock Meter Rubbing fastness

Instrument to determine colour fastness to rubbing, fitted with a digital reading counter. The instrument is supplied complete with a rubbing dowel with 1,6 cm diameter, a dowel with 1,9x2,54 cm dimensions, (each dowel is equipped with a proper weight, in order to reach 9 N), and one set of crocking clothes.

Optional:

1 set of no. 500 pieces of cotton crocking clothCode198.422Grey scale A03Code267AReference standards: UNI EN ISO 105 X12, AATCC 165,

M&S C8, NEXT 6

Weight: 8 kg

Dimensions: (L) 670 x (W) 220 x (H) 210 mm

Electric Crock Meter Rubbing fastness

Electric model to determine colour fastness to rubbing, fitted with a digital counter. The Crock Meter is supplied complete with a rubbing dowel with 1,6 cm diameter, a dowel with 1,9x2,54 cm dimensions, one pre-installed weight (to reach 9 N), and one set of crocking clothes.

Optional:	Code	198.422
no. 500 pieces of cotton crocking cloth	Code	267A
Grey scale		

Reference standards: UNI EN ISO 105 X12, AATCC 8, AATCC 165, M&S C8, NEXT 6

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 18 kg

Dimensions: (L) 610 x (W) 220 x (H) 300 mm

Forced Ventilation Conditioning Oven

251G

2540

High-tech oven suitable for crimp checking in yarns and for checking the dimensional stability of fabrics in hot air.

Suitable for the hot cleaning of mechanical spinnerets, for drying and heating of any type of textiles.

Supplied complete with temperature digital regulator and two grid-type shelves made of stainless steel.

Forced ventilation of the heating air.

Operating temperature range: from room temperature to +280°C. Accuracy: \pm 1°C.

Available models:

Inside dimensions (L) 408 x (W) 372 x (H) 422mm		
Capacity: 60 litres. Weight: 40 kg	Code	251G
Inside dimensions (L) 498 x (W) 477 x (H) 512mm		
Capacity: 120 litres. Weight: 50 kg	Code	251H
Inside dimensions (L) 593 x (W) 522 x (H) 797mm		
Capacity: 250 litres. Weight: 90 kg	Code	251P

Power supply: 230 Vac or 400 Vac, 50/60 Hz





Sample Press Lab

1750A

Hydraulic punch cutting machine with high cutting capacity. Ideal to cut textile, leather, rubber and soft plastic specimens, to be used for different types of testing (such as strength, weight per square metre, flexion, bursting tests, etc.).

Cutting capacity: 16.000 kg

Maximum cutting surface: 400x800 mm

Maximum cutting stroke: 80 mm

Cutting device can be activated by means of a safety button.

Reference standards: ASTM, ISO, DIN, AFNOR and UNI standards only.

Power supply: 400 V, three-phase, 50/60 Hz Weight: 870 kg Dimensions: (L) 980 x (W) 900 x (H) 1410 mm

Optional:

Punching knives

Circular, rectangular and square, with straight and jagged blade - different dimensions on demand.

Punch thickness: 30 mm

Cutting stroke: about 5 mm



Hoff-Lab Press

3370B

Vaporising ironing machine to check the dimensional stability of orthogonal and knitted fabrics during ironing tests.

Hoff-Lab Press is equipped with a PLC device which controls the automatic pressing, sample vaporising and suction cycles. The test is set through a control panel, where some preset programs are available. The operator can anyway create and save new programs.

Suction is performed by the lower board. Suction depressure complies with international standards and can be certified by third parties.

Ironing board dimensions: 600 x 800 mm

Optional:

Electric boiler for vapour production, code 3370 2.

Reference standards: DIN 53894-2, NF G07 212, ASTM D2724, IWS TM 290, JIS L1096 method H2, H3, H4, JIS L1909

Available also model **Code 3370A**, which conforms to all the same standards, except for DIN and NF standards.

Power supply: 400 Vac, 50 Hz, three-phase + N Weight: 310 kg Dimensions: (L) 1400 x (W) 1000 x (H) 1600 mm





code 312B



Scorch Fastness Sublimation tester 312A

To determine colour fastness to hot pressing and dry heat and to perform sublimation tests.

Heating plates dimensions: 125x125 mm (5"x5"). Temperature range: from +125°C to +230°C. Pressure: 4 kPa

Reference standards: ISO 105 X11, AATCC 117, 133, BS 1006

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 15 kg

Dimensions: (L) 260 (W) 460 (H) 240 mm

Available also **Code 312B**: 5 plates, dimensions: 102x29 mm, (4"x1.13").

Perspirometer Incubator

257A

251L



Instruments to check:

colour fastness to perspiration, in compliance with the following standards: UNI EN ISO 105- E04; BS 1006; BS EN 20105; AATCC 15; IWS TM 175

Colour fastness to swimming pool and sea water, in compliance with the following standards UNI EN ISO 105 E01; BS 1006; BS EN 20105; AATCC 106; AATCC 107; IWS TM 6.

Colour yellowing to phenol, in compliance with ISO and AATCC standards.

The system is composed of:

Code 257A - Perspirometer; standard weight of 5 kg, optional;

set of plexiglas 21 plates (100x40 mm each), complete with one metallic container

Code 251L - Incubator cabinet with measuring, temperature range: from +5°C above room temperature to +80°C; accuracy: $\pm 0.5^{\circ}$ C at 37°C

Optional:

Multifibre fabrics DW 010 (ISO 105 e BS 1006)	Code	257.424
Grey scale A03 (ISO 105 e BS 1006) to assess colour staining	Code	267A
Grey scale A02 (ISO 105 e BS 1006) to assess colour fastness	Code	267C
Kit of chemicals to reproduce acid and alkaline perspiration (in compliance with ISO, BSi, IWS, IWS TM)	Code	257.8
Weight: 4,54 kg for AATCC standard	Code	257.4
Set of glass: 10 plates (100x40x3 mm each)	Code	257.18
Colour yellowing to phenol Kit for ISO (105x18 mm)	Code	257.10
Weight: 5 kg for ISO standard	Code	257.20

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 45 kg

Inner dimensions: (L) 300 x (W) 240 x (H) 300 mm Outside dimensions: (L) 550 x (W) x 350 x (H) 420 mm



picture: 257A + 251L

Sun Lab Light fastness

325A

Equipment for the analysis of the colour fastness to the light of a 1500W Xenon lamp.

The following parameters are monitored, controlled and stabilized:

- temperature measured on the specimen with the B.S.T. method;
- · lamp irradiance.

Possibility of specimen irradiance (one filter is included at customer's choice); other filters are supplied as optional:

UV 310 filter + IR (exposure behind the window) Code 325.34

UV 280 filter + IR (outdoors exposure) Code 325.38

UV 280 filter (outdoors exposure) Code 325.42

UV 310 filter (exposure behind the window) Code 325.46

Timer included.

Optional: see optional accessories available for Xenon Lab **Code 325E.**

Reference standards: ISO 105, BS 1006

Power supply: 230 Vac, 50/60 Hz, single-phase Weight: 29 kg Dimensions: (L) 750 x (W) 390 x (H) 400 mm



Xenon Lab Light fastness

325E

Equipment for the analysis of the colour fastness to the light of a 1500W Xenon lamp in a chamber with preset humidity, controlled by ultrasonic device.

- The following parameters are monitored, controlled, and stabilized:
- \cdot temperature;
- · humidity;
- · lamp irradiance.

Filter UV 310 nm for the simulation of indoors conditions. Possibility of specimen irradiance: see Sun Lab (**code 325A**) description, for filter specifications.

Optional:

Set of Blue standard scale for light fastness (50 units) Code	325.2
Humidity test control fabric (Htc)	Code	325.30
Grey scale type A02	Code	267C
Set of 3 sample holders 100 (x3)	Code 1	93A.100

Reference standards: ISO 105 B02 (except A.1.4); BS 1006

Power supply: 230 V, 50/60 Hz Weight: 60 kg

Dimensions: (L) 750 x (W) 390 x (H) 1000 mm Specimen tray dimensions: 280 x 200 mm





Wascator

High precision washing machine officially acknowledged as a standard reference for washing tests on fabrics. Wascator is also suitable for checking effects of washing detergents and chemical products.

Equipped with microprocessor for setting several programs of different functioning cycles.

Optional:

Polyester makeweight	Code	310.72
Stability template and percentage ruler		
for checking the dimensional stability	Code	310.14
Memory card UNI EN ISO 6330	Code	310B.90

ECE / IEC detergents available on demand

Reference standards: UNI EN ISO 6330, UNI EN ISO 5077, IWS TM 31, IEC 456, M&S P1, M&S P1A, M&S P3A, M&S P12, M&S P91, M&S P99, M&S P99A, M&S P134

Power supply: 230 Vac or 400 Vac, 50 or 60 Hz, three-phase Weight: 195 kg

Dimensions: (L) 720 x (W) 690 x (H) 1315 mm

Tumble Dryer

3111

310B

Recommended model to dry samples washed with Wascator, Code 310B.

Capacity: 5 kg - Timer: 99,99 min.

Equipped with electronic processor for accurate temperature control within $\pm 1^{\circ}$ C.

Reference standards: UNI EN ISO 6330, ISO 6330, AATCC 135, M&S P1A, M&S P3A, M&S P3B, M&S P4A, M&S P12, M&S P91, M&S P99A, M&S P134

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Weight: 35 kg $\,$

Dimensions: (L) 600 x (W) 600 x (H) 850 mm

Dry Cleaning Machine 310F

Dry cleaning machine internationally acknowledged as a standard reference to check the dimensional stability of fabrics to dry washing.

Equipped with an electronic device for the control of the different washing programs.

Complete with drying system.

Reference standards: EN ISO 3175, AATCC 158

Power supply: 400 Vac, 50/60 Hz, three-phase Net weight: 1200 kg Dimensions: (L) 1460 x (W) 2100 x (H) 2000 mm





Top Loading Home Washer зтон

Washing machine with loading system from the top, to simulate domestic washing cycles. Equipment selected and certified by AATCC.

Reference standards: AATCC 88B, AATCC 88C, AATCC 124, AATCC 130, AATCC 135, AATCC 142, AATCC 143, AATCC 150, AATCC 159, AATCC 179

Power supply: 115 Vac, 60 Hz or 230 Vac, 50 Hz Weight: 58 kg Dimensions: (L) 699 x (W) 686 x (H) 1006 mm

Front-loading Home Tumble Dryer 3111B

Tumble dryer machine with loading system from the front, to dry samples after their washing with the Top Loading Home Washer (code 310H).

Equipment selected and certified by AATCC, to perform domestic drying cycles.

Reference standards: AATCC 88B, AATCC 88C, AATCC 124, AATCC 130, AATCC 135, AATCC 142, AATCC 143, AATCC 150, AATCC 159, AATCC 179

Power supply: 115 Vac, 60 Hz or 230 Vac, 50 Hz Weight: 55 kg Dimensions: (L) 737 x (W) 717 x (H) 1090 mm

Autowash II Wash-Dry colour fastness 311L

Instrument to determine the colour fastness to dry-cleaning or washing. Fitted with a computerised electronic temperature controller, accuracy $\pm 1^{\circ}$ C. It can be used also for atmospheric dyeing up to $+98^{\circ}$ C. Structure wholly made of very strong stainless steel.

Dual speed selection: 40 rpm (as requested by the standards for colour fastness) and 22 rpm (for dyeing tests).

Model designed to contain up to 8 interchangeable beakers of 550 cc or 1200 cc for colour fastness testing, according to the specific standard (European or American) in use. Also suitable for soaping.

Available on demand a 16-position model, code 311M.

Optional:

Stainless steel beakers550 cc for colour fastnessCode311L.18Stainless steel beakers1200 cc for colour fastnessCode311L.20Base for instrument placementCode311L.22

Reference standards: UNI EN ISO: 105 C06, 105 C08, 105 C09, 105 C10, 105 C12, 105 D01, 105 E03, 105 E12, 105 X05, 11643; AATCC: 61-1A, 61-2A-3A-4A-5A, 86, 132, 151, 190; M&S: C4A, C5, C37, P3B; IUF 434, NEXT TM2. Officially approved by Marks & Spencer (M&S) Power supply: 400 Vac, 50/60 Hz, three-phase + N Weight: 135 kg

Dimensions: (L) 1025 x (W) 757 x (H) 1127 mm









Grey Scales

For checking colour staining and fastness, according to ISO 105 (BS 1006).

Available in two models:

Grey scale A02 for colour change tests	Code	267C
Grey scale A03 for colour staining tests	Code	267A
AATCC grey scales for colour staining test and fo tests are also available:	r colour 1	fastness
AATCC scale for colour change tests	Code	267D

AATCC scale for colour staining tasts	Codo	2675
AATOO Scale for colour stairing lesis	COUC	2076

Blue Scale

325.2

Set of 50 cards in pure wool, each with 8 sticked blue scale gradations.

To test colour fastness of cloths exposed to light, in accordance with ISO Standard 105 (BS 1006), ATCC $\,$



Suitable for colour staining tests according to ISO 105 standards (BS 1006).

Available in the following versions:

F01 Wool (10x4 cm - 50 pcs.)	Code	323.8
F02 cotton (limbric) - (10x4 cm - 50 pcs.)	Code	323.6
F02 Viscose (1 m)	Code	323.10
F03 Polyamide (Nylon 6.6, 1 m)	Code	323.12
F04 Polyester (1 m)	Code	323.14
F05 Acrylic (1 m)	Code	323.16
F09 Cotton rubbing cloth (Lawn) - (500 pcs.)	Code	198.422
D01 Cotton for dry cleaning (Drill) - (1 m)	Code	323.4

Multifibre DW 010

257.424

Standard fabrics for colour staining tests, according to ISO 105 (BS 1006) norms, F10. The fabrics are made of fibres: secondary cellulose, acetate, cotton, polyamide, polyester, acrylic and wool. Supplied in packages of 10 m length each.

Multifibre TV

257.426

Same as DW010 **Code 257.424**, but for washing tests at high temperature.









AATCC/ISO Crease Appearance Replicas 310.94

Set of 5 standard references to visually evaluate the crease in the fabrics after washing.

Reference standards: UNI EN ISO 15487, ISO 7769 , AATCC 88C, AATCC 143, M&S P134



AATCC/ISO Seam Smoothness Appearance Replicas 310.96

Set of standard reference for the smoothness appearance of seams in fabrics after cleansing.

Reference standards: UNI EN ISO 15487, ISO 7770, AATCC 143

AATCC/ISO Smoothness Appearance Replicas 310.74

Set of 6 standard references for the visual assessment of the fabric smoothness after washing.

Reference standards: AATCC 124, AATCC 143, M&S P91, M&S P134, ISO 7768

Soap Powder

310.10

To perform tests of colour fastness to washing, as per the ISO 105 (BS 1006), CO1-CO5 standards.

ECE/IEC Reference Detergent

Detergent with or without bleaching agents, to be used for the colour fastness tests to washing, following the ISO standards.

ECE without phosphate (A) 2 kg	Code	310.32
ECE with phosphate (B) 2 kg	Code	310.4
IEC without phosphate (A) 2 kg	Code	310.16
IEC with phosphate (B) 2 kg	Code	310.40





Vapour Permeability Tester 3122

To check the resistance of textiles to water vapour penetration.

The system is composed of:

- no. 3 pots complete with covers and gaskets
- no. 1 laboratory glass dryer, diameter 300 mm
- no. 1 25 ml pipette
- no. 1 kg silica gel

Electronic balance not included

Reference standards: UNI 4818 - 26

Weight: 20 kg Dimensions: (L) 400 (W) 400 (H) 400 mm

Water Vapour Tester

Instrument to analyse the water vapour permeability of leather, industrial fabrics and all permeable materials. Sample rotation speed: 75 \pm 5 rpm. Ventilation system: with 3 blades rotating at 1400 \pm 100 rpm.

3395

The equipment is composed of:

set of rotating beaker holder for 6 positions, with rapid release system

6 glass beakers

protection system for the operator

Reference standards: UNI EN 420 International Standard for testing "Protective Gloves", UNI EN ISO 20344 and UNI EN ISO 14268 for leather, UNI EN 13515

Power supply: 230 Vac, 50/60 Hz Weight: 25 kg Dimensions: (L) 550 x (W) 650 x (H) 500 mm

Static Lab 291B

Equipment suitable for checking the static electricity properties of clothes, protective fabrics, shoe fabrics and leather materials.

It is composed of:

electronic control panel for the digital reading of the static electricity values (Ohm)

connecting cables

measuring heads for the static electricity reading as regards both the "surface" and "vertical" methods

Reference standards: UNI EN 1149-1, UNI EN 1149-2, AATCC 76

Note: before the static electricity measurement, sample has to be conditioned at +23°C \pm 1° and R.H. 25% \pm 5%, with Climatest (**Code 1722**).

Power supply: 230 Vac, 50/60 Hz, single-phase Weight: 5 kg Dimensions: (L) 500 x (W) 300 x (H) 300 mm





Glove Cut Tester

3394A

Equipment for checking the resistance of protective cloths to cutting. Suitable to perform tests on protective gloves against accidents, according to the EN 388 standard.

Accessories supplied with the equipment:

- · 1 pack of aluminium paper with 0.01 mm thickness
- · 1 pack of paper (filter) 65 g/m²
- · 1 pack of reference fabric
- · 2 sample holders
- · 10 blades

Reference standards: UNI EN 388 6.2.2 (2017), UNI EN 13594

Power supply: 230 Vac, 50/60 Hz Weight: 25 kg Dimensions: (L) 500 x (W) 300 x (H) 420 mm



Linear Cut Resistance Tester 3394B

Instrument suitable to measure the resistance to cutting on protective clothing. Designed to perform tests also on protective gloves, according to the international Standards. Equipped with moveable 9-position sample holder, suitable to perform multiple tests - on the same specimen - with different applicable forces, in order to collect data to define the resistance to cutting by sharp objects.

The instrument is supplied with:

- · 1 set of combinable weights to reach forces up to 61 N
- · 20 Standard blades
- · 1 Standard calibration neoprene sheet
- · 1 Bi-adhesive tape, 1 roll
- · 1 Aluminium foil, 1 roll

Reference standards: UNI EN ISO 13997, UNI EN 388 6.3 (2017), ASTM F2992/F2992M

Power supply: 230 Vac, 50 Hz. Weight: 39 kg Dimensions: (L) 800 x (W) 390 x (H) 400 mm

Impact Abrasion Lab 2563

Laboratory instrument suitable to:

Determine quality of protective suits like motor rider suits (both one-piece and detached), gloves etc. Made to protect motorbikers from injuries caused by impact against the road surface.

Determine the resistance to abrasion of wrist, knee, elbow and hand protections.

Supplied complete with timer (in seconds), meter counter for abrasion, device to apply a pressure of 49N onto specimens, waste suction device, and safety device for the operator.

Reference standards: UNI EN 13595-2, UNI EN 13594, UNI EN 14120, UNI EN 388 6.6 (2017)

Power supply: 400 Vac, 50/60 Hz, three-phase + N Compressed air supply: 5 bar Net weight: 250 kg Dimensions: (L) 1500 x (W) 500 x (H) 1500 mm



ISO Flammability Lab







Instrument to determine the flammability resistance of textiles and the flame propagation rate onto **vertically** oriented textile materials.

Suitable to test:

protective fabrics;

technical fabrics in general;

clothes and furnishing fabrics.

The instrument can be also used with toys, as well as with both natural and artificial leather.

ISO Flammability Lab is fully **automatic**, since it is equipped with a PLC that controls and records the movement of the burner, the distance of the same from the samples, and the flame propagation time from one set distance to the other one. The PLC is equipped with 1 RS232 serial port for connection with Personal Computer, and for printing of test results.

Optional:

Computer - Software - Printer

Radiator (**Code 3392E.40**) to analyse the flammability resistance of textile materials exposed to the heat of a radiator (as required by the EN 13772).

Reference standards: UNI EN ISO 15025, UNI EN ISO 6940, UNI EN ISO 6941, UNI EN 13772, UNI EN 407, UNI EN 1101, UNI EN 1102, UNI EN 1103, UNI EN ISO 14116, UNI EN ISO 14878

Power supply: 115 Vac or 230 Vac, 50/60 Hz Net weight: 50 kg Dimensions: (L) 650 x (W) 750 x (H) 1200 mm



68

45° Flammability Tester 3392c

Laboratory instrument to determine the flammability resistance of fabrics exposed to a flame with an angle of 45°.

Automatic model with timer (in seconds) that automatically stops the flame application at the end of the pre-set time, and consequently measures the flame propagation time to reach the target zone.

Made of stainless steel.

Transparent panel made of fire-resistant glass.

Reference standards: CS 191-53 (CFR 1610), ASTM D1230, NFPA 702, CA TB 117 (2000), BIFMA, FED STD 191A TM 5908, 16 CFR 1610

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Net weight: 20 kg Dimensions: (L) 400 x (W) 350 x (H) 500 mm



Horizontal Flammability Tester 3392D

Automatic instrument to determine the flammability resistance of all kinds of materials used both in the automotive and aircraft industries.

Equipped with a timer (in seconds) to control the ignition time.

Reference standards: UNI EN ISO 17074, UNI ISO 3795, ASTM D5132, FMVSS 302, FAA, BOEING, AIRBUS, SAE J 369, CMVSS 302, JISD 1201, FAR Part 25 Appendix F Part 1

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Net weight: 12 kg

Dimensions: (L) 450 x (W) 200 x (H) 450 mm



Automatic instrument to determine the flammability resistance to a vertical flame of apparel fabrics, protective fabrics, curtains and children's sleepwear.

Equipped with a timer (in seconds) to control the ignition time.

Reference standards: ASTM D6413, ASTM F1506, NFPA 1971, NFPA 1975, NFPA 1976, NFPA 1977, NFPA 1981, NFPA 2112, FAR Part 25 Appendix F Part 1, CPAI 84 - Tent walls and tops, Federal Test method 5903, BOEING BSS 7230, AIRBUS AITM 2.0002

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase Net weight: 38 kg Dimensions: (L) 330 x (W) 340 x (H) 850 mm





Sweating Guarded Hot Plate



Highly accurate instrument to determine the physiological "comfort" of fabrics.

Testing is performed by means of a transparent hot plate, called "skin model", that simulates the process of heat and humidity transfer occurring in proximity of the human skin. It provides the following data:

Thermal resistance (RCT) with scale from 0.002 to 2.0 m² K/W

Resistance to steam (RET) with scale from 5 to 1000 m² Pa/W

Index of permeability to steam (IMT)

Permeability to steam (Wd)

Max flux 1100 W/m²

The instrument is supplied complete with:

Hot plate for fabric specimens up to 8"x 8"

Electronic interface with heating and conditioning sensors

Heating device of the "skin model" plate

Air control device

Sensors for the measuring of air speed, temperature and relative humidity.

Personal computer complete with operating software

To carry out testing, the use of Climatest (Code 1722S) is necessary.

Reference standards: ISO EN 11092, UNI EN 31092, ASTM D 1518, ASTM F 1868, NFPA 1971.

Power supply: 115 Vac or 230 Vac, 50/60 Hz Weight: 52 kg Dimensions: (L) 660 x (W) 610 x (H) 610 mm





Integrated Sweating Guarded Hot Plate System

The Sweating Guarded Hot Plate, or "Skin Model", is used to produce accurate, repeatable measurements of thermal resistance (Rct) and vapour permeability (Ret) for textiles as per UNI EN ISO 11092, ASTM F1868 e ASTM D1518 (Option II).

The iSGHP-8.2 and iSGHP-10.5 systems include Hot Plate with integral sweating surface, computer controlled variable airflow rates, gravity fed fluid supply system, and ambient temperature and humidity probes.

The system's integrated chamber features an insulated stainless steel interior and a compact, space-efficient design.

Its ergonomic layout yields a comfortable working height of approximately 42" (107cm) above the floor, and other thoughtful touches include a high intensity LED cabinet light, a removable top shelf for the preconditioning of fabric samples, and a large insulated door with viewing window.

For sweating tests the SGHP Hot Plate utilizes the chamber's water source, and a unique porous wicking assembly on both Hot Plate and guard ring ensures a uniform wetted surface.

Adjustable (motorized) plate height easily accommodates a variety of sample thicknesses, and our ThermDAC control and data logging software makes testing very simple.

Reference standards:

UNI EN ISO 11092, ISO 13029, ASTM F1868, ASTM D1518 Option II, ASTM D1518 Option I*, GB/T 11048, CEN/TR 16422:2012

Power supply: 220/240 Vac, 50/60 Hz, single-phase Weight: 448 kg Dimensions: (L) 910 x (W) 990 x (H) 1780 mm







Thermetrics Advanced Thermal Measurement Technology



Performance

Ensemble Weight Durability Don/Doff Smart Garments Active Cooling Systems Comfort Heat Stress

Breathability Wicking Tactile Properties

ANDI Thermal Manikin

Sweating thermal manikin for advanced thermal comfort research, with exclusive features: Dynamic Heatflux Sensing and Active-Cooling; ANDI can measure both positive and negative heatflux (heat loss and heat gain) and respond to changing environmental conditions with unprecedented speed and accuracy.

Standard sweating model with 35 independent thermal zones.

Testing temperature range: -40°C to +50°C.

Precision carbon-epoxy shell with embedded sensor and resistance wire heating elements.

ANDI system includes manikin, control electronics, laptop PC, and ThermDAC control software.

Options:

- · ManikinPC physiological control software
- · Active Cooling technology, with external chiller
- · Dynamic Heatflux Sensing (DHS)
- Sweating system with fluid distribution system, reservoir, and wicking fabric skin layer
- · Walking motion stand
- · External breathing system

Automotive Thermal Comfort

STAN Seat Test Manikin

"Back and buttocks" (8 thermal zones), developed to evaluate the thermal comfort and moisture management properties of automobile seating.

HVAC Automotive Manikin

Complete turn-key system for measuring the effect of vehicle heating and air conditioning designs on passenger comfort.

Drying Rate Tester DRT201

To determine the drying rate of a fabric based on the evaporative rate that occurs when a predetermined amount of water is absorbed into a fabric that is positioned upon a heated plate set to human skin temperature, and then dried with constant controlled airflow (in compliance with **AATCC 201**).

Available also "Drying Rate Tester DRT200" (Air Flow Meter), in compliance with AATCC 200.






MISCELLANEOUS

p 74	Electronic Tachometer	Code	1810C
p 74	Electronic Tachometer	Code	1810G
p 74	Electronic Tachometer	Code	1810E
p 74	Electronic Tachometer	Code	1810H
p 75	Tensiometer Zivy		
p 75	Electronic Tensiometer ZEF/ZED		
p 75	Warp Tensiometer DXK model		
p 76	Electronic Tensiometer DTS		
p 76	Electronic Tensiometer ETB		
p 76	Mechanical Tensiometer DX2		
p 76	Mechanical Tensiometer ZF2/ZD2		
p 77	Stroboscope		
p 77	Strobo Lab	Code	186H
p 77	Battery Powered Digital Stroboscope	Code	186F
p 77	Phonometer	Code	243B
p 78	Thermo-anemometer	Code	287C
p 78	Electronic Psychrometer	Code	288C
p 78	Sling Psychrometer	Code	196B
p 78	"Assmann" Psychrometer	Code	196C
p 79	Writing Thermo-hygrograph	Code	180B
p 79	Digital Thermometer	Code	244B
p 79	Optical Pyrometer	Code	296D
p 79	Orbital Shaker	Code	3125A
p 80	"Sartorius" analytic Balance	Code	165.702
p 80	"Sartorius" precision Balance	Code	165.704
p 80	"Sartorius" multi-purpose Balance	Code	165.708
p 80	Thermo Balance	Code	165.502
p 81	Digital Force Tester	Code	194D
p 81	Refractometer	Code	266A
p 81	Yarn Meter	Code	298E
p 81	Yarn Meter	Code	298D
p 82	Portable pH-meter	Code	322C
p 82	Bench pH-Meter	Code	322L
p 82	Viscosimeter	Code	3220
p 82	UV Lamp	Code	189A
p 83	Portable Thickness Gauges		
p 83	Ultrasonic Cleaning Baths		
p 83	Melt-Flow Index	Code	339B





Electronic Tachometer 1810c

Digital contact reading from 0.1 to 25000 rpm and from 0.02 to 3810 m/min.

Available measuring scales for values reading:

revolutions per minute, revolutions per hour, yard/min., yard/ hour, m/hour, feet and inches per min. and per hour.

Selectable length: cm, m, inches, feet and yards.

Storage capacity of the last 10 measurements including minimum and maximum values.

Power supply: 1,5 V battery x 2



Electronic Tachometer 1810G

Contact reading.

Measuring range: from 1 to 25000 rpm and from 0,1 to 3810 m/min with ± 1 rpm accuracy (from 1 to 599 rpm), and $\pm 0,01\%$ of reading (from 600 to 25000 rpm).

Complete with accessories (equipped with a set of rubber ferrules).

Power supply: 1,5 V battery x 3



Optical model for contact and non-contact measurements. Measuring range from 6 to 99999 rpm with ± 1 revolution accuracy (non-contact) and from 1 to 25000 rpm (contact). Measuring distance: 2 m max.

Equipped with built-in memory system for the storage of the last 10 measurements, minimum and maximum values included.

Power supply: 1,5 V battery x 2



Electronic Tachometer 1810H

Optical model for contact and non-contact measurements. Measuring range from 6 to 99.999 rpm with ± 1 rpm accuracy (from 6 to 599 rpm), and $\pm 0,01\%$ of reading (from 600 to 99999 rpm).

Measuring distance: 2 m max.

Also a model for non-contact measurements only is available (code 1810L).

Power supply: 1,5 V battery x 3



Tensiometer Zivy

Available in the following scales:	
TEN 5K 1 - 5 g (cN)	
TEN 12K 2 - 12 g (cN)	
TEN 30K 5 - 30 g (cN)	
TEN 70K 10 - 70 g (cN)	
TEN 120K 20 - 120 g (cN)	
TEN 170K 50 - 170 g (cN)	

Code	182A
Code	182B
Code	182C
Code	182E
Code	182F
Code	182G



Electronic Tensiometer ZEF/ZED

Digital reading. Recommended for knitting, hosiery, warping and assembling machines.

Available reading scales:

from 0,5 to 100 cN with 0,1 cN accuracy	Code	1836
from 1 to 500 cN with 1 cN accuracy	Code	1837



Warp Tensiometer DXK

To determine correct tension on warps both statically and dynamically.

10 mm measuring roller, to simultaneously measure 5 or 10 yarns.

Available in 3 versions:

DXK-300 with reading scale from 20 to 300 cN	Code	2876
DXK-1000 with reading scale from 100 to 1000 \ensuremath{cN}	Code	2877
DXK-2000 with reading scale from 200 to 2000 cN	Code	2878

For dynamic analysis, the Tensiometer

DXK complete with the optional "Air Damping"

tension absorber is recommended Code 286.126



Electronic Tensiometer DTS

Digital reading. Particularly suitable for winding, twisting, warping machines. Distance between the two outer rollers:

66 mm. Reading of the real working tension and of tensionpeaks. Equipped with rollers suitable for yarn speed up to 2000 m/min. As optional, special rollers are available for yarn speeds up to 5000 m/min.

Available reading scales:

from 0,2 to 200 cN	Code	195A
from 0,5 to 500 cN	Code	195B
from 10 to 1000 cN	Code	195C
from 20 to 2000 cN	Code	195D

Other "DTX" models, equipped with software and USB cable, are available on demand.

Electronic Tensiometer ETB

Digital reading. Recommended for texturizing machines, automatic winders, warping machines and any textile machine where the lack of space makes the measuring difficult. Distance between the two rollers: 24 mm.

Available models:

tension range from 0.3 to 100.0 cN with steel guide rollers suitable for yarn speed up to 2000 m/min. Resolution: 0.1 cN Code 1830F

tension range from 2.0 to 200.0 cN with steel guide rollers suitable for yarn speed up to 2000 m/min. Resolution: 0.1 cN Code 1830G

tension range from 2.0 to 500.0 cN with steel guide rollers suitable for yarn speed up to 2000 m/min. Resolution: 0.1 cN Code 1830H

Other models are also available on demand:

 $\ensuremath{\mathsf{ETPB}}$ models, with ceramic heads, suitable for yarn speed up to 6000 m/min.

ETX & ETPX models, equipped with specific software and USB cable

Mechanical Tensiometer DX2

Particularly suitable for winders, twisters and warping machines. The following reading scales are available:

from 10 to 50 cN	Code	286N
from 20 to 200 cN	Code	286P
from 20 to 400 cN	Code	286A
from 50 to 1000 cN	Code	286D
from 200 to 2000 cN	Code	286W
from 400 to 5000 cN	Code	286Y

Mechanical Tensiometer ZF2/ZD2

Particularly suitable for knitting and hosiery machines. The following reading scales are available:

from 1 to 5 cN	Code	286F
from 1 to 12 cN	Code	2865
from 3 to 30 cN	Code	286G
from 5 to 50 cN	Code	286H
from 10 to 100 cN	Code	2861
from 20 to 200 cN	Code	286L







Stroboscope

Particularly suitable for the control of ring spinning frames, twisting, knitting and hosiery machines.

Analog reading, scale from 200 to 18000 rpm Power supply: 115 Vac or 230 Vac, 50/60 Hz	Code	186A
Digital reading, scale from 30 to 30000 rpm Power supply: 115 Vac or 230 Vac, 50/60 Hz	Code	186M
Digital reading, scale from 30 to 30000 rpm Power supply: rechargeable battery	Code	186L
Analog reading, scale from 200 to 18000 rpm Power supply: rechargeable battery	Code	186D



186H

Particularly suitable for the control of ring spinning frames, twisting, knitting and hosiery machines.

Digital reading stroboscope with built-in rechargeable battery. Complete with a special high luminosity lamp, for easier reading, even in case of high frequencies.

Measuring range: from 300 to 25000 rpm. Accuracy: ±1 rpm.

Power supply: 100 up to 230 Vac, 50/60 Hz, single-phase

Battery Powered Digital Stroboscope

186F

Special model with high luminosity lamp.

Particularly suitable for the control of ring spinning frames, twisting, knitting and hosiery machines.

Reading range: from 40 to 35000 rpm with ± 1 rpm accuracy. Complete with built-in rechargeable battery.

Power supply: 115 Vac or 230 Vac, 50/60 Hz, + battery

Phonometer

243B

Digital instrument of class 2. Measuring range: from 30 to 130 dB. Features: instantaneous measuring, max hold and battery level.

Power supply: 1,5 V battery x 3









Thermo-anemometer 287C

Digital reading. Particularly suitable for the measurement of temperature and air speed of the air conditioning and fan-ventilation systems in textile factories.

Recommended for spinning facilities, both natural and man-made fibres.

Measuring range: air speed from 0.01 to 30 m/sec (\pm 3% of reading or \pm 0.015 m/s whichever is aerated); air temperature from -17,8°C to +93,3°C (\pm 0,3°C).

Equipped with telescopic probe

Power supply: 1,5 V battery x 4

Electronic Psychrometer 288c

For the direct reading of the environmental temperature and humidity. Measuring range: from -20° C to $+80^{\circ}$ C, and from 5% to 98% R.H. (±1,5% R.H. accuracy in range from 10% to 90%). Digital reading.

Different probes available. Standard probe **code 288C.10** (to be added).

As optional the following calibration solutions are available:

33,0% Rh solution	Code	288C.4
75,4% Rh solution	Code	288C.6

Power supply: 9 V battery

Sling Psychrometer

196B

Portable model for reading of environmental humidity percentage and temperature.

Reading scale: from 0 to 100% R.H., and from 0°C to +45°C. Measuring principle by means of a dry bulb thermometer and a wet bulb thermometer.

"Assmann" Psychrometer 1960

Portable model with dry or wet bulb to determine the environmental humidity and temperature.

Endowed with two mercury thermometers with measuring range from 0°C to +50°C (\pm 0.2°C accuracy).

Complete with electric fan.

Power supply: 1,5 V battery





Writing Thermo-hygrograph 180B

For the graphic reading of the environmental temperature and humidity.

Measuring range from: 0°C to +40°C (\pm 1,5% accuracy) and from 0 to 100% R.H. (accuracy \pm 3% from 0 to 40% R.H.; \pm 5% from 40 to 100% R.H.).

Complete with 52 weekly diagrams.

The measuring principle is achieved by means of a bundle of hair.

Power supply: 1,5 V battery

Digital Thermometer 244B

Measuring range: $-200^{\circ}C + 1370^{\circ}C$ Resolution: $+0,1^{\circ}C$ up to $+600^{\circ}C$ Instrument accuracy: $\pm 0,5^{\circ}C$ from 0 to $+200^{\circ}C, \pm 2^{\circ}C$ from $+200^{\circ}C$ to the end scale and from $-0,1^{\circ}C$ to $-200^{\circ}C$.

Optional probes suggested:

contact probe KTP 745	Code	244B.2
immersion probe, KTP 741	Code	244B.4

Other types of probes are available on request.

Power suply: 1,5 V battery x 3

Optical Pyrometer

296D

3125A

Electronic infrared thermometer for temperature measurement at distance.

Particularly suitable for ring spinning frames, twisting, texturizing and dyeing machines.

Measuring scale: from -50°C to +1000°C, with \pm 2% reading accuracy.

Adjustable emission with maximum peak function and acoustic alarm.

Power supply: 1,5 V battery x 2

Orbital Shaker

Orbital shaker suitable for extraction of aqueous pH from textile materials.

Equipped with a tray with 4 adjustable separators coated with rubber, and timer.

Tray dimensions: 550 x 450 mm.

Adjustable electronic speed control from 50 to 230 rpm.

Power supply: 230 Vac, 50 Hz, single-phase Weight: 20 kg Dimensions: (L) 600 x (W) 550 x (H) 230 mm









MISCELLANEOUS



"Sartorius" analytic Balance 165.702

120 g weighing capacity and 0,0001 g accuracy. Digital reading. RS232 interface port. Pan size: ø 90 mm.

Power supply: 100 up to 230 Vac, 50/60 Hz, single-phase Weight: 4.8 kg Dimensions: (L) 230 x (W) 303 x (H) 330 mm

"Sartorius" precision Balance 165.704

320 g weighing capacity and 0,001 g accuracy. Digital reading. RS232 interface port. Pan size: ø 115 mm.

Power supply: 100 up to 230 Vac, 50/60 Hz, single-phase Weight: 3.6 kg Dimensions: (L) 230 x (W) 303 x (H) 136 mm

"Sartorius" multi-purpose **Balance**

165.708

820 g weighing capacity and 0,01 g accuracy. Digital reading. RS232 interface port. Pan size: ø 150 mm.

Power supply: 100 up to 230 Vac, 50/60 Hz, single-phase Weight: 2.6 kg Dimensions: (L) 230 x (W) 303 x (H) 87 mm

Other models available with higher capacity and with larger pan (180 x 180 mm).

Thermo Balance

165.502

150 g weighing capacity and 0,001 g accuracy. RS232 interface port. Infrared heating system, with range from $+40^{\circ}$ C to $+220^{\circ}$ C. Main available information: dry material weight %, lost weight of the material (mg), humidity %.

Power supply: 100 up to 230 Vac, 50/60 Hz, single-phase Weight: 5.5 kg Dimensions: (L) 213 x (W) 320 x (H) 181 mm

Other models are available on request.







Digital Force Tester

To check the traction and compression strength; provided with USB / RS 232 port. Available measuring units: N, kgf, lbf. Measuring range: from 0 to 50 N (0.01N accuracy). Different models are available on demand. Recommended for the control of the drawing rollers in the spinning frames. Complete with built-in rechargeable battery.

Power supply: 115 up to 230 Vac, 50/60 Hz, rechargeable battery Weight: 0.4 kg Dimensions: (L) 215 x (W) 65 x (H) 51 mm

Refractometer

266A

194D

Portable model, suitable for the determination of the percentage of dry material in a solution, such as sizing. Measuring range: 0 - 32%.



298E

298D

Equipment to measure yarn tension, length and speed at the machine.

Maximum yarn speed: 1000 m/min.

Length measuring unit: metre or inch (± 1 cm or ± 1 inch accuracy). Tension measuring range: 0-50 cN.

Power supply: rechargeable battery

Yarn Meter

Reading of two different values: yarn speed: from 0,1 to 1999 m/min.

quantity of absorbed yarn during a pre-set time: from 0.02 to 99999 m.

Digital reading.

Power supply: 9 V battery x 2 Weight: 0.22 kg

MISCELLANEOUS



Portable pH-meter

Measuring scale: from 0.00 to 14.00 pH. Probes on request. Accuracy: 0.01 pH. Application range: from -50°C to +400°C.

Power supply: 1,5 V battery x 3

Bench pH-Meter

322L

322C

Digital bench instrument, suitable for pH measurement in laboratory. Equipped with user interface and wide colour display (for real-time graph display). Very high accuracy and wide measuring range (from -2 to 20 pH).

Bench pH-Meter is supplied with pH electrode, temperature probe, electrode holder, buffer solutions, cleaning solution, pipette, and 12 VDC adapter. Glass beakers (100 ml and 250 ml capacity) are available as optional.

Temperature Range: from -20.0 to 120.0°C / from -4.0 to 248.0°F / from 253.15 to 393.15 K.

Temperature Resolution: 0.1°C / 0.1°F / 0.1 K.

USB / RS232 communication ports for PC connection.

For fabric pH evaluation, a specific "**Aqueous Extract pH Kit**" is available.

Power supply: 120-230 Vac, 50-60 Hz Weight: 1,2 kg Dimensions: (L) 160 x (W) 231 x (H) 94 mm

Viscosimeter

3220

Rotational viscosimeter for quick measurement of viscosity in compliance with ISO 2555 and with ASTM standards. 54 Rotational speeds (between 0.01 rpm and 200 rpm). Accuracy: ±1%.

Viscosity range:

(R-Version): 100 mPas - 40.000.000 mPas	Code	3220A
(L-Version): 15 mPas - 6.000.000 mPas	Code	3220
Power supply: 115 up to 230 Vac, 50/60 Hz		

UV Lamp

189A

"Triwood" portable model with 6 lamps of 6 W each. Suitable for the visual assessment of fibre impurities in yarn lots (for example: cotton with polyester).

Power supply: 230 Vac, 50/60 Hz, single-phase





Portable Thickness Gauges

The following models are available: Measuring depth: 200 mm. Thickness reading range: 30 mm Accuracy: 0,1 mm Code 188F Measuring depth: 200 mm. Thickness reading range: 10 mm Accuracy: 0,01 mm Code 188R Measuring depth: 30 mm. Thickness reading range: 1 mm Accuracy: 0,001 mm Code 188G Measuring depth: 200 mm. Thickness reading range: 30 mm Accuracy: 0,01 mm Code 1887

Other models are available on request



Ultrasonic Cleaning Baths

Ultrasonic bath for a quick and perfect cleaning of glassware, spinnerets and texturing disks eliminating the toughest impurities hidden in holes and hollows.

The following models are available:

45 litres-22 kg - (L) 500 x (W) 300 x (H) 520 mm Code 3101C

28 litres-13.4 kg - (L) 505 x (W) 300 x (H) 200 mm Code 3101B

3 litres-3.2 kg - (L) 240 x (W) 137 x (H) 100 mm Code 3101A

Complete with heating system from +30°C to +85°C

Optional: lid, internal basket and detergent to clean the internal basket.

Power supply: 115 Vac or 230 Vac, 50/60 Hz, single-phase



Melt-Flow Index

339B

Automatic model to determine the fluidity index of thermoplastic materials exposed to heat.

The instrument carries out a volumetric procedure (MVI) and, by means of an optical system, determines the volume of the material extruded during a pre-set period of time. Equipped with a microprocessor that acquires, elaborates and displays both the single values and the average values (max. 12 values), and RS232 port for PC connection.

Temperature range: from $+50^{\circ}$ C to $+400^{\circ}$ C with $\pm 0,1^{\circ}$ C accuracy.

Reference standards:

UNI EN ISO 1133, UNI 5640, DIN 53735, AFNOR 51/016, ASTM D1238 meth. A-B, ASTM D2116, ASTM D3159, ASTM D3364, BS 2782/105 C PART.7 meth. A.

Power supply: 230 Vac, 50/60 Hz, single-phase Weight: 30 kg Dimensions: (L) 420 x (W) 330 x (H) 530 mm



Certificates and Calibrations

In 2004 MESDAN S.p.A. obtained from Det Norske Veritas (DNV) the certification about Quality and Environmental Management System, in conformity with UNI EN ISO 9001 and UNI EN ISO 14001, with validity for design, manufacture and calibration of textile laboratory instruments.

Since then, MESDAN S.p.A. has successfully undergone through the periodical audits of the Certifying Body and complete re-assessment of certification of its Quality Systems.



"MESDAN LAB" can issue:

- · Calibration Reports, complying with **UNI EN ISO 9001** (in some countries contractual calibration service for complete laboratories is available on demand).
- · Calibration Certificate, complying with ISO 17025 (Accredia ILAC).

MESDAN S.p.A. closely supports its international clientele in more than 70 countries by means of a capillary network of sales and service stations, which can provide qualified technical assistance.

Mesdan affiliations











CERTIFICATO DI ACCREDITAMENTO

Accreditation Certificate

ACCREDITAMENTO N. ACCREDITATION N.

279T REV. 00

EMESSO DA ISSUED BY

DIPARTIMENTO LABORATORI DI TARATURA

SI DICHIARA CHE WE DECLARE THAT

MESDAN LAB SERVICE

SEDE PRINCIPALE/HEADQUARTER • Via Beretta, 20 25086 PUEGNAGO DEL GARDA (BS) - Italia

È CONFORME AI REQUISITI DELLA NORMA MEETS THE REQUIREMENTS OF THE STANDARD UNI CEI EN ISO/IEC 17025:2005 - Requisiti generali per la competenza dei laboratori di prova e taratura

EN ISO/IEC 17025:2005 - General requirements for the competence of testing and calibration laboratories

QUALE Laboratorio di taratura (LAT)

AS Calibration laboratory (LAT)

Data di 1^ª emissione 1st issue date 07-03-2019

Ing. Rosalba Mugno Il Direttore di Dipartimento The Department Director

Data di Modifica Modification date Data di Scadenza Expiry date 06-03-2023

Ing. Giuseppe Rossi Il Presidente The President

Pag.1 di 1

L'accreditamento attesta che il Laboratorio ha la competenza per operare quale Centro di taratura ACCREDIA per le grandezze, i campi e le incertezze di misura riportati nella tabella allegata al presente certificato di accreditamento. Il presente certificato non è da ritenersi valido se non accompagnato dalla tabella allegata e può essere sospeso o revocato in qualsiasi momento nel caso di inadempienza accertata da parte di ACCREDIA. La validità dell'accreditamento può essere verificata sui sito WEB (www.accredia.lt) o richiesta direttamente al Dipartimento di competenza. Questo Laboratorio è accreditato in accordo alla norma internazionale UNI CEL ISO/IEC 17025:2005. L'accreditamento dimostra che il laboratorio possiede competenza tecnica per lo scopo definito e che opera secondo un sistema di gestione (si veda il comunicato congiunto ISO-ILAC-IAF dell'Aprile 2017).

Pott. Filippo Trifiletti

Il Direttore Generale

The General Director

secondo un sistema di gestione (si veda il comunicato congiunto ISO-ILAC-IAF dell'Aprile 2017). Accreditation attests that the Laboratory has the competence to operate as calibration Centre of ACCREDIA, for the physical quantities, the range and uncertainty of measurement reported in the table attached to the present accreditation certificate. The present certificate is valid only if associated to the annexed schedule, and can be suspend or withdrawn at any time in the event of non fulfilment as ascertained by ACCREDIA. The in force status of the accreditation may be checked in the WEB site (www.accredia.it) or on direct request to relevant Department. This laboratory is accredited in accordance with the recognised International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated April 2017).

ACCREDIA

Sede operativa: Strada delle Cacce, 91|10135 Torino - Italy |Tel. +39 011 328461|Fax +039 011 3284630 Sede legale: Via Guglielmo Saliceto, 7/9 |00161 Roma - Italy |Tel. +39 06 8440991|Fax +39 06 8841199 info@accredia.it |www.accredia.it |Partita IVA - Codice Fiscale 10566361001

MD-17-DT Rev. 02





In addition to laboratory equipment, Mesdan is famous for its wide range of Yarn Joining solutions, such as:



Hand Knotters















MESDAN S.P.A. - VIA MASSERINO, 6 25080 PUEGNAGO DEL GARDA (BS) - ITALY PHONE +39 0365 653142 FAX +39 0365 651011 sales@mesdan.it - **www.mesdan.com**

